



SAFETY DATA SHEET

Amber Cavity Wax Aerosol

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Cavity Wax Aerosol - Amber
Product number TACW-A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Underbody coat.

1.3. Details of the supplier of the safety data sheet

Supplier International Applications Limited
18 Wildmere Road
Wildmere Industrial Estate
Banbury
Oxfordshire
OX16 3JU
Tel: +44 (0) 1295 274004
Fax: +44 (0) 1295 211268
Email: sales@international-applications.com

1.4. Emergency telephone number

Emergency telephone 44 (0) 1295 274004 (Hours 08:30 - 17:00 Mon to Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture**Classification****Physical hazards**

Aerosol 1 - H222, H229

Health hazards

Skin Irrit. 2 - H315 STOT SE 3 - H336

Environmental hazards

Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC)

F+; R12. Xi; R38. N; R51/53. R66, R67

Human health

Vapours and spray/mists in high concentrations are narcotic.

Environmental

The product contains a substance which is toxic to aquatic organisms.

Physicochemical

Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is extremely flammable. Vapours may form explosive mixtures with air.

2.2. Label elements**Pictogram**

Amber Cavity Wax Aerosol



Signal word

Danger

Hazard statements

- H222 Extremely flammable aerosol.
- H229 Pressurised container: may burst if heated
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing vapour/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Supplemental label information

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains

HEPTANE, HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

Supplementary precautionary statements

- P264 Wash contaminated skin thoroughly after handling.
- P273 Avoid release to the environment.
- P321 Specific treatment (see medical advice on this label).
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P391 Collect spillage.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with national regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PETROLEUM GASES, LIQUEFIED CAS number: 68476-85-7 EC number: 270-704-2	30-60%
Classification Flam. Gas 1 - H220 Press. Gas, Compressed - H280	Classification (67/548/EEC or 1999/45/EC)

Amber Cavity Wax Aerosol

HEPTANE	10-30%
CAS number: 64742-49-0 EC number: 927-510-4 REACH registration number: 01-2119475515-33-XXXX	
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 STOT SE 3 - H336 Aquatic Chronic 2 - H411	
HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)	10-30%
CAS number: 64742-82-1 EC number: 919-446-0	
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	5-10%
CAS number: 64742-47-8 EC number: 265-149-8	
Classification	Classification (67/548/EEC or 1999/45/EC)
Asp. Tox. 1 - H304	
XYLENE	<1%
CAS number: 1330-20-7 EC number: 215-535-7 REACH registration number: 01-2119488216-32-XXXX	
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304	Xn; R65, R48/20/21/22, R20/21. Xi; R36/37/38. R10
ethylbenzene	<1%
CAS number: 100-41-4 EC number: 202-849-4	
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 2 - H225 Acute Tox. 4 - H332	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any

Amber Cavity Wax Aerosol

discomfort continues.

Inhalation

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.

Ingestion

Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.

Skin contact

Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.

Eye contact

Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

Protection of first aiders

First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information

See Section 11 for additional information on health hazards.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards

Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during firefighting

Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions

Avoid discharge into drains.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for

Amber Cavity Wax Aerosol

additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.

Advice on general occupational hygiene

Wash promptly with soap and water if skin becomes contaminated.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

PETROLEUM GASES, LIQUEFIED

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

HEPTANE (CAS: 64742-49-0)

DNEL

Consumer - Oral; Long term systemic effects: 149 mg/kg/day
Consumer - Dermal; Long term systemic effects: 149 mg/kg/day
Workers - Dermal; Long term systemic effects: 300 mg/kg/day
Consumer - Inhalation; Long term systemic effects: 447 mg/m³
Workers - Inhalation; Long term systemic effects: 2085 mg/m³

XYLENE (CAS: 1330-20-7)

DNEL

Consumer - Dermal; Long term systemic effects: 108 mg/kg/day
Workers - Dermal; Long term systemic effects: 180 mg/kg/day
Consumer - Inhalation; Short term local effects: 174 mg/m³
Consumer - Inhalation; Short term systemic effects: 174 mg/m³
Workers - Inhalation; Short term systemic effects: 289 mg/m³
Workers - Inhalation; Short term local effects: 289 mg/m³
Consumer - Inhalation; Long term systemic effects: 14.8 mg/m³
Workers - Inhalation; Long term systemic effects: 77 mg/m³

8.2. Exposure controls

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

Hand protection

No specific hand protection recommended.

Amber Cavity Wax Aerosol

Other skin and body protection

Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.

Respiratory protection

No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Aerosol.

Colour

Amber.

Odour

Solvent.

Odour threshold

No information available.

pH

No information available.

Melting point

No information available.

Initial boiling point and range

-41 (-41 TO 210)°C @

Flash point

-40°C CC (Closed cup).

Evaporation rate

No information available.

Evaporation factor

No information available.

Flammability (solid, gas)

No information available.

Upper/lower flammability or explosive limits

Lower flammable/explosive limit: 0.6 % Upper flammable/explosive limit: 9.5 %

Vapour pressure

No information available.

Vapour density

No information available.

Relative density

0.682

Solubility(ies)

Insoluble in water.

Partition coefficient

No information available.

Auto-ignition temperature

225°C

Decomposition Temperature

No information available.

Viscosity

No information available.

Oxidising properties

Amber Cavity Wax Aerosol

No information available.

9.2. Other information

Other information

None.

SECTION 10: Stability and reactivity

10.1. Reactivity

No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability

The product may not be stable under some conditions of storage or use.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid

None known.

10.6. Hazardous decomposition products

None at ambient temperatures.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation

May cause drowsiness or dizziness. Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.

Skin contact

Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

Eye contact

Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health hazards

No known chronic or acute health risks.

Route of entry

Inhalation Skin and/or eye contact

Toxicological information on ingredients.

Amber Cavity Wax Aerosol

HEPTANE

Acute toxicity - oral

Acute toxicity oral (LD50 mg/kg)

5,001.0

Species

Rat

ATE oral (mg/kg)

5,001.0

Acute toxicity - dermal

Acute toxicity dermal (LD50 mg/kg)

2001.0

Species

Rabbit

ATE dermal (mg/kg)

2001.0

HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

Acute toxicity - oral

Acute toxicity oral (LD50 mg/kg)

15,001.0

Species

Rat

ATE oral (mg/kg)

15,001.0

Acute toxicity - dermal

Acute toxicity dermal (LD50 mg/kg)

3401.0

Species

Rat

ATE dermal (mg/kg)

3401.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC50 vapours mg/l)

13101.0

Species

Rat

ATE inhalation (vapours mg/l)

13101.0

Amber Cavity Wax Aerosol

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

Acute toxicity - oral

Acute toxicity oral (LD50 mg/kg)

5,001.0

Species

Rat

ATE oral (mg/kg)

5,001.0

Acute toxicity - dermal

Acute toxicity dermal (LD50 mg/kg)

2001.0

Species

Rabbit

ATE dermal (mg/kg)

2001.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC50 vapours mg/l)

5.29

Species

Rat

XYLENE

Acute toxicity - oral

Acute toxicity oral (LD50 mg/kg)

4,300.0

Species

Rat

ATE oral (mg/kg)

4,300.0

Acute toxicity - dermal

Acute toxicity dermal (LD50 mg/kg)

3200.0

Species

Rabbit

ATE dermal (mg/kg)

1100

Acute toxicity - inhalation

ATE inhalation (vapours mg/l)

11.0

ethylbenzene

Acute toxicity - inhalation

ATE inhalation (vapours mg/l)

11.0

SECTION 12: Ecological Information

12.1. Toxicity

Amber Cavity Wax Aerosol

Ecological information on ingredients.

HEPTANE

Acute toxicity - fish

NOEC, : 1-10 mg/l, Fish

Acute toxicity - aquatic plants

LOEC, : 10-100 mg/l, Algae

Acute toxicity - microorganisms

LOEC, : 1-10 mg/l, Activated sludge

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

Acute toxicity - fish

LOEC, : >100 mg/l, Fish

Acute toxicity - aquatic plants

LOEC, : >100 mg/l, Algae

Acute toxicity - microorganisms

LOEC, : >100 mg/l, Activated sludge

XYLENE

Acute toxicity - fish

LOEC, : >1 - <10 mg/l, Fish

Acute toxicity - aquatic plants

LOEC, : >1 - <10 mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability

No data available.

12.3. Bioaccumulative potential

Partition coefficient

No information available.

12.4. Mobility in soil

Mobility

No data available

12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

Dispose of waste product or used containers in accordance with local regulations

Disposal methods

Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

Amber Cavity Wax Aerosol

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels**14.4. Packing group**

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



Yes.

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations**

The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

EU legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Amber Cavity Wax Aerosol

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 22/12/2014

Revision 1

SDS number 5217

Hazard statements in full

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: may burst if heated
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.