

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: ETABLEND SPOT BLENDER

1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses: professional use.
 Application of the substance / the mixture Thinner, Diluent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Alexport Company
 Pontou 26, P.C. 546 28, Thessaloniki, Greece,
 Tel: +30 2310 501814, Fax: +30 2310 524 771
 www.etalon.gr

Further information obtainable from: info@alexport.gr

1.4 Emergency telephone number: 122 or call your doctor/local poison center

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS08

Signal word Danger

Hazard-determining components of labelling:

xylene

n-butyl acetate

hydrocarbons, C9, aromatics

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.06.2015

V- 1

Revision: 12.06.2015

Trade name: ETABLEND SPOT BLENDER

(Contd. of page 1)

Hazard statements

- H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H304 May be fatal if swallowed and enters airways.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.

| Dangerous components: | | |
|--|--|---------|
| CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29 | n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336 | 25-50% |
| CAS: 763-69-9 EINECS: 212-112-9 Reg.nr.: 01-2119463267-34 | ethyl 3-ethoxypropionate ⚠ Flam. Liq. 3, H226 | 5-15% |
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32 | xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; ⚠ Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; ⚠ Acute Tox. 4, H332; ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2, H319; ⚠ STOT SE 3, H335 | 5-15% |
| EC number: 918-668-5 Reg.nr.: 01-2119455851-35 | hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336 | 5-15% |
| CAS: 108-10-1 EINECS: 203-550-1 Reg.nr.: 01-2119473980-30 | 4-methylpentan-2-one ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 4, H332; ⚠ Eye Irrit. 2, H319; ⚠ STOT SE 3, H335 | 2.5-10% |
| CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47 | 2-butoxyethyl acetate ⚠ Acute Tox. 4, H312; ⚠ Acute Tox. 4, H332 | 1-5% |

Additional information: For the wording of the listed risk phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Take affected persons out of danger area and lay down.

(Contd. on page 3)

Trade name: ETABLEND SPOT BLENDER

(Contd. of page 2)

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

5.3 Advice for firefighters**Protective equipment:**

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Avoid contact with the eyes and skin.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.06.2015

V- 1

Revision: 12.06.2015

Trade name: ETABLEND SPOT BLENDER

(Contd. of page 3)

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.**Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

7.3 Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection****Additional information about design of technical facilities:** No further data; see item 7.**8.1 Control parameters**

| Ingredients with limit values that require monitoring at the workplace: | |
|--|---|
| 123-86-4 n-butyl acetate | |
| WEL (Great Britain) | Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm |
| 1330-20-7 xylene | |
| WEL (Great Britain) | Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV |
| IOELV (EU) | Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin |
| 108-10-1 4-methylpentan-2-one | |
| WEL (Great Britain) | Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm Sk, BMGV |
| IOELV (EU) | Short-term value: 208 mg/m ³ , 50 ppm Long-term value: 83 mg/m ³ , 20 ppm |
| 112-07-2 2-butoxyethyl acetate | |
| WEL (Great Britain) | Short-term value: 332 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Sk |
| IOELV (EU) | Short-term value: 333 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Skin |
| DNELs | |
| 123-86-4 n-butyl acetate | |
| Dermal | DNEL 7 mg/kg bw/day (long-term - systemic effects, workers) |
| Inhalative | DNEL 960 mg/m ³ (acute - systemic effects, workers) 960 mg/m ³ (acute - local effects, workers) 480 mg/m ³ (long-term - systemic effects, workers) |

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.06.2015

V- 1

Revision: 12.06.2015

Trade name: ETABLEND SPOT BLENDER

(Contd. of page 4)

| | | |
|--|------|---|
| | | 480 mg/m ³ (long-term - local effects, workers) |
| 763-69-9 ethyl 3-ethoxypropionate | | |
| Dermal | DNEL | 102 mg/kg bw/day (long-term - systemic effects, workers) |
| | | 102 mg/cm ² (long-term - local effects, workers) |
| Inhalative | DNEL | 610 mg/m ³ (long-term - systemic effects, workers) |
| | | 610 mg/m ³ (long-term - local effects, workers) |
| 1330-20-7 xylene | | |
| Dermal | DNEL | 180 mg/kg bw/day (long-term - systemic effects, workers) |
| Inhalative | DNEL | 289 mg/m ³ (acute - systemic effects, workers) |
| | | 289 mg/m ³ (acute - local effects, workers) |
| | | 77 mg/m ³ (long-term - systemic effects, workers) |
| | | 77 mg/m ³ (long-term - local effects, workers) |
| hydrocarbons, C9, aromatics | | |
| Dermal | DNEL | 25 mg/kg bw/day (long-term - systemic effects, workers) |
| Inhalative | DNEL | 150 mg/m ³ (long-term - systemic effects, workers) |
| 108-10-1 4-methylpentan-2-one | | |
| Dermal | DNEL | 11.8 mg/kg bw/day (long-term - systemic effects, workers) |
| Inhalative | DNEL | 208 mg/m ³ (acute - systemic effects, workers) |
| | | 208 mg/m ³ (acute - local effects, workers) |
| | | 83 mg/m ³ (long-term - systemic effects, workers) |
| | | 83 mg/m ³ (long-term - local effects, workers) |
| 112-07-2 2-butoxyethyl acetate | | |
| Dermal | DNEL | 102 mg/kg bw/day (acute - systemic effects, workers) |
| | | 102 mg/kg bw/day (long-term - systemic effects, workers) |
| Inhalative | DNEL | 775 mg/m ³ (acute - systemic effects, workers) |
| | | 333 mg/m ³ (acute - local effects, workers) |
| | | 133 mg/m ³ (long-term - local effects, workers) |
| PNECs | | |
| 123-86-4 n-butyl acetate | | |
| PNEC | | 0.18 mg/l (freshwater environment) |
| | | 0.018 mg/l (marine environment) |
| | | 0.36 mg/l (intermittent releases) |
| | | 0.981 mg/kg (freshwater sediment environment) |
| | | 35.6 mg/l (sewage treatment plants) |
| 763-69-9 ethyl 3-ethoxypropionate | | |
| PNEC | | 0.0609 mg/l (freshwater environment) |
| | | 0.00609 mg/l (marine environment) |
| | | 0.609 mg/l (intermittent releases) |
| | | 0.419 mg/kg (freshwater sediment environment) |
| | | 0.048 mg/kg (soil) |
| | | 50 mg/l (sewage treatment plants) |
| 1330-20-7 xylene | | |
| PNEC | | 0.327 mg/l (freshwater environment) |
| | | 12.46 mg/kg (freshwater sediment environment) |
| | | 2.31 mg/kg (soil) |
| | | 6.58 mg/l (sewage treatment plants) |

(Contd. on page 6)

Trade name: ETABLEND SPOT BLENDER

(Contd. of page 5)

| | |
|--|---|
| 108-10-1 4-methylpentan-2-one | |
| PNEC | 0.6 mg/l (freshwater environment) 0.06 mg/l (marine environment) 1.5 mg/l (intermittent releases) 8.27 mg/kg (freshwater sediment environment) 0.83 mg/kg (marine sediment environment) 27.5 mg/l (sewage treatment plants) |
| 112-07-2 2-butoxyethyl acetate | |
| PNEC | 0.304 mg/l (freshwater environment) 0.0304 mg/l (marine environment) 0.56 mg/l (intermittent releases) 2.03 mg/kg (freshwater sediment environment) 0.203 mg/kg (marine sediment environment) 0.68 mg/kg (soil) 90 mg/l (sewage treatment plants) |
| Ingredients with biological limit values: | |
| 1330-20-7 xylene | |
| BMGV (Great Britain) | 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid |
| 108-10-1 4-methylpentan-2-one | |
| BMGV (Great Britain) | 20 µmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one |

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Keep ignition sources away - Do not smoke.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:

Protective gloves

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 7)

Trade name: ETABLEND SPOT BLENDER

(Contd. of page 6)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (EN 374).

Material of gloves

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

PVA gloves

Recommended thickness of the material: $\geq 0,7$ mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove materialValue for the permeation: Level 6 ≥ 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Appearance:**

| | |
|-------------------------|-----------------|
| Form: | Fluid |
| Colour: | Colourless |
| Odour: | Characteristic |
| Odour threshold: | Not determined. |

pH-value: Not applicable.

Change in condition

| | |
|-------------------------------------|---------------|
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 114 °C |
| | Undetermined. |

Flash point: 28 °C

Flammability (solid, gaseous): Not applicable.

Decomposition temperature: Not determined.

Auto-ignition temperature: Not determined.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

| | |
|---------------|------------|
| Lower: | 0.7 Vol % |
| Upper: | 15.0 Vol % |

Vapour pressure at 20 °C: 10.7 hPa

Density at 20 °C: 0.9 g/cm³

Vapour density: Not determined.

Evaporation rate: Not determined.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.06.2015

V- 1

Revision: 12.06.2015

Trade name: ETABLEND SPOT BLENDER

(Contd. of page 7)

| | |
|---|--|
| Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| Partition coefficient (n-octanol/water): | Not determined. |
| Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

10.1 Reactivity No decomposition if used according to specifications.

10.2 Chemical stability No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Reacts with alkali, amines and strong acids.

Reacts with oxidising agents.

Fumes can combine with air to form an explosive mixture.

10.4 Conditions to avoid Protect from heat and direct sunlight.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| | | |
|--|----------|-------------------------|
| LD/LC50 values relevant for classification: | | |
| 123-86-4 n-butyl acetate | | |
| Oral | LD50 | 10760 mg/kg (rat) |
| Dermal | LD50 | 10760 mg/kg (rat) |
| | | >14000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 23.4 mg/l (rat) |
| 763-69-9 ethyl 3-ethoxypropionate | | |
| Oral | LD50 | 4309 mg/kg (rat) |
| Dermal | LD50 | 4080 mg/kg (rabbit) |
| 1330-20-7 xylene | | |
| Oral | ATE | >2000 mg/kg (-) |
| Dermal | ATE | 1466.67 mg/kg (-) |
| Inhalative | ATE | 12.09 mg/l (-) (vapour) |
| hydrocarbons, C9, aromatics | | |
| Oral | LD50 | 3592 mg/kg (rat) |
| Dermal | LD50 | >3160 mg/kg (-) |
| Inhalative | LC50/4 h | > 6193 mg/l (rat) |
| 108-10-1 4-methylpentan-2-one | | |
| Oral | LD50 | 2080 mg/kg (rat) |
| Dermal | LD50 | 16000 mg/kg (rab) |
| Inhalative | LC50/4 h | 10-20 mg/l (rat) |

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.06.2015

V- 1

Revision: 12.06.2015

Trade name: ETABLEND SPOT BLENDER

(Contd. of page 8)

| 112-07-2 2-butoxyethyl acetate | | |
|---------------------------------------|----------|---------------------|
| Oral | LD50 | 1880 mg/kg (rat) |
| Dermal | LD50 | 1500 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 11 mg/l (ATE) |

Primary irritant effect:**Skin corrosion/irritation**

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)****Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure**

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information**12.1 Toxicity**

| Aquatic toxicity: | |
|--|---|
| 123-86-4 n-butyl acetate | |
| EC50/48 h | 44 mg/l (daphnia) |
| EC50/72 h | 675 mg/l (algae) |
| LC50/96 h | 18 mg/l (Pimephales promelas) |
| TT/16 h | 115 mg/l (Pseudomonas putida) |
| 763-69-9 ethyl 3-ethoxypropionate | |
| EC50/48 h | 785 mg/l (Daphnia magna) |
| EC50/72 h | >114.86 mg/l (Pseudokirchnerella subcapitata) |
| LC50/96 h | 60.9 mg/l (fish) |
| 1330-20-7 xylene | |
| EC50/24 h | 96 mg/l (microorganisms) |
| EC50/48 h | >1-10 mg/l (Daphnia magna) |
| IC50/72 h | 2.2 mg/l (algae) |
| LC50/96 h | 2.6 mg/l (fish) |
| hydrocarbons, C9, aromatics | |
| EC50/10 min | >99 mg/l (microorganisms) |
| EC50/48 h | 6.14 mg/l (Daphnia magna) |
| EL50/48 h | 3.2 mg/l (Daphnia magna) |
| ErC50/96 h | 9.2 mg/l (fish) |
| ErL50/72 h | 2.9 mg/l (Pseudokirchnerella subcapitata) |
| 112-07-2 2-butoxyethyl acetate | |
| EC50/24 h | >100 mg/l (Daphnia magna) |
| EC50/72 h | >100 mg/l (Scenedesmus subspicatus) |
| LC50/48 h | 10-100 mg/l (Leuciscus idus melanotus) |

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.06.2015

V- 1

Revision: 12.06.2015

Trade name: ETABLEND SPOT BLENDER

(Contd. of page 9)

| | |
|---|---|
| 12.2 Persistence and degradability | |
| 123-86-4 n-butyl acetate | |
| Biodegradation | 83 % (readily biodegradable) (OECD 301 D, 28 d, aerobic) |
| 763-69-9 ethyl 3-ethoxypropionate | |
| Biodegradation | 100 % (readily biodegradable) (CO2 Evolution Test, 28 d) |
| 1330-20-7 xylene | |
| Biodegradation | >60 % (readily biodegradable) (OECD 301 F, 28 d, aerobic) |
| hydrocarbons, C9, aromatics | |
| Biodegradation | 78 % (readily biodegradable) (OECD 301 F, 28 d, aerobic) |
| 112-07-2 2-butoxyethyl acetate | |
| Biodegradation | >70 % (readily biodegradable) (OECD 301C, 28d) |
| 12.3 Bioaccumulative potential | |
| 123-86-4 n-butyl acetate | |
| BCF | 15.3 (-) |
| log Pow | 2.3 (-) |
| 763-69-9 ethyl 3-ethoxypropionate | |
| log Pow | 1.35 (-) |
| 1330-20-7 xylene | |
| BCF | 25.9 (-) |
| log Pow | 3.15 (-) |
| 12.4 Mobility in soil | |
| 123-86-4 n-butyl acetate | |
| log Koc | 1.27 (-) |
| 763-69-9 ethyl 3-ethoxypropionate | |
| Koc | 32.78 (-) |
| log Koc | 1.52 (-) |

Additional ecological information:**General notes:**

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11* | waste paint and varnish containing organic solvents or other dangerous substances

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.06.2015


V- 1

Revision: 12.06.2015

Trade name: **ETABLEND SPOT BLENDER**

(Contd. of page 10)

SECTION 14: Transport information

| | | | | | |
|--|---|-------|---|-------|---|
| 14.1 UN-Number ADR, IMDG, IATA | UN1263 | | | | |
| 14.2 UN proper shipping name ADR IMDG, IATA | 1263 PAINT PAINT | | | | |
| 14.3 Transport hazard class(es) ADR, IMDG, IATA | <div style="text-align: center;">  </div> <table style="width: 100%;"> <tr> <td style="width: 60%;">Class</td> <td>3</td> </tr> <tr> <td>Label</td> <td>3</td> </tr> </table> | Class | 3 | Label | 3 |
| Class | 3 | | | | |
| Label | 3 | | | | |
| 14.4 Packing group ADR, IMDG, IATA | III | | | | |
| 14.5 Environmental hazards: Marine pollutant (IMDG): | No | | | | |
| 14.6 Special precautions for user Danger code (Kemler): EMS Number: | Warning: Flammable liquids. 30 F-E,S-E | | | | |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. | | | | |
| Transport/Additional information: | | | | | |
| ----- | | | | | |
| ADR | | | | | |
| Limited quantities (LQ) | 5L | | | | |
| Transport category | 3 | | | | |
| Tunnel restriction code | D/E | | | | |
| ----- | | | | | |
| IMDG | | | | | |
| Limited quantities (LQ) | 5L | | | | |
| UN "Model Regulation": | UN1263, PAINT, 3, III | | | | |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 12)

Trade name: ETABLEND SPOT BLENDER

(Contd. of page 11)

Relevant phrases

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

Sources European Chemicals Agency, <http://echa.europa.eu/>