

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **Windscreen Adhesive / ETW-9000**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **One component adhesive for the automotive industry.**

Identified Uses	Industrial	Professional	Consumer
SEALANTS AND ADHESIVES FORMULATIONS IN INDUSTRY	SU: 10. ERC: 2. PROC: 3, 4, 5, 8a, 8b, 9. PC: 1.	-	-
INDUSTRIAL APPLICATIONS OF SEALANTS AND ADHESIVES	SU: 17, 19. ERC: 5, 8b. PROC: 10, 8a, 8b. PC: 1.	SU: 17, 19. ERC: 5, 8b. PROC: 10, 8a, 8b. PC: 1.	-
CHEMICAL SUBSTANCE USE IN LABORATORY, INDUSTRIAL	PROC: 15. PC: 1, 21.	-	-

1.3. Details of the supplier of the safety data sheet

Name **Alexport Company**
 Full address **Pontou 26, P.C. 546 28, Thessaloniki, Greece,**
 District and Country **Tel: +30 2310 501814, Fax: +30 2310 524 771**
www.etalon.gr
info@alexport.gr

e-mail address of the competent person responsible for the Safety Data Sheet

1.4. Emergency telephone number

For urgent inquiries refer to **122 or call your doctor/local poison center**

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Respiratory sensitization, category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.

SECTION 2. Hazards identification. ... / >>**2.2. Label elements.**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
EUH204 Contains isocyanates. May produce an allergic reaction.

Precautionary statements:

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P280 Wear protective gloves / protective clothing / eye protection / face protection.
P284 [In case of inadequate ventilation] wear respiratory protection.
P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.
P342+P311 If experiencing respiratory symptoms: call a POISON CENTER / doctor / . . .
P362+P364 Take off contaminated clothing and wash it before reuse.

Contains: DIPHENYLMETHANE-4,4'-DIISOCYANATE
 HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.**3.1. Substances.**

Information not relevant.

3.2. Mixtures.

Contains:

Identification. Conc. % Classification 1272/2008 (CLP).

HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER

CAS. 28182-81-2 4,5 - 5 Acute Tox. 4 H332, STOT SE 3 H335, Skin Sens. 1 H317

EC. 931-274-8

INDEX.

Reg. no. 01-2119485796-17

DIPHENYLMETHANE-4,4'-DIISOCYANATE

CAS. 101-68-8 0,89 - 1 Carc. 2 H351, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315,
 STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317, Note 2 C

EC. 202-966-0

INDEX. 615-005-00-9

Reg. no. 01-2119457014-47-XXXX

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.**4.1. Description of first aid measures.**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

SECTION 4. First aid measures. ... / >>

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health.

Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 10

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 16 grudnia 2011r
SWE	Sverige	Occupational Exposure Limit Values, AF 2011:18
	TLV-ACGIH	ACGIH 2014

DIISONONYL PHTHALATE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
WEL	GBR	5			

DIPHENYLMETHANE-4,4'-DIISOCYANATE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	0,05		0,05		
MAK	DEU	0,05		0,05		SKIN.
MAK	DEU	0,05		0,05		INHAL.
VLA	ESP	0,052	0,005			
VLEP	FRA	0,1	0,01	0,2	0,02	
TLV	GRC	0,2		0,2		
NDS	POL	0,03		0,09		
MAK	SWE	0,03	0,002	0,05 (C)	0,005 (C)	
TLV-ACGIH		0,051	0,005			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect your hands with work gloves, category III (ref. standard EN 374). For the final choice of material you need to assess the type of use. In case of contact for the short term or as protection against splashes, use gloves made of nitrile (0.3mm thickness, permeation time >480 min.).

In the event of continued exposure use butyl rubber gloves (0.4mm thickness, permeation time > 480 min.). Contaminated gloves should be removed.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

In case of exceeding the threshold value (eg, TLV-TWA) of the substance or one or more of the substances present in the product, it is advisable to wear a mask with filter type A for organic vapors, the class (1, 2 or 3) must be chosen according to the limit concentration of use (1000, 5000 or 10000 ppm) (ref. standard EN 14387).

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.**9.1. Information on basic physical and chemical properties.**

Appearance	paste
Colour	black
Odour	characteristic
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	> 100 °C.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	1,36 Kg/l
Solubility	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	250000 - 350000 cps
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information.

VOC (Directive 2010/75/EC) :	0
VOC (volatile carbon) :	0

SECTION 10. Stability and reactivity.**10.1. Reactivity.**

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.**11.1. Information on toxicological effects.**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Inhalation of this product causes sensitization, which may then give rise to a series of inflammatory episodes, most of all characterized by obstruction and affecting the respiratory system. Sometimes, sensitization phenomena arise together with evident rhinitis and asthma. Damages to the respiratory system depend on the inhaled quantity, on the product concentration in the working environment and on the exposure time.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurries, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurry skin, dryness, ulcerations and skin thickening prevail during the chronic phase.

SECTION 11. Toxicological information. ... / >>

This product contains isocyanates. Producer's specifications are as follows: Ready-to-use products containing isocyanates may irritate mucosae, particularly those of the respiratory system, and may give rise to hypersensitivity reactions. Vapour or aerosol inhalation may lead to sensitization. Please take all the measures used for all solvent-containing products while manipulating isocyanate-containing products. Avoid vapour and aerosol inhalation. People with allergic or asthmatic precedents or subject to respiratory disorders should not handle products containing isocyanates.

This product contains sensitizing substance/s and may cause allergic reactions.

HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER

LD50 (Oral). > 2500 mg/kg Rattus sp.

LD50 (Dermal). > 2000 mg/kg Oryctolagus sp.

DIPHENYLMETHANE-4,4'-DIISOCYANATE

LD50 (Oral). > 2000 mg/kg Rattus sp.

LD50 (Dermal). > 9400 mg/kg Oryctolagus sp.

LC50 (Inhalation). 2,24 mg/l Rattus sp.

SECTION 12. Ecological information.**12.1. Toxicity.****HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPOLYMER**

EC50 - for Algae / Aquatic Plants. > 1000 mg/l/72h Scenedesmus sp.

Chronic NOEC for Fish. > 100 mg/l Danio rerio

Chronic NOEC for Crustacea. > 100 mg/l Daphnia magna

DIPHENYLMETHANE-4,4'-DIISOCYANATE

LC50 - for Fish. > 1000 mg/l/96h Danio rerio

Chronic NOEC for Algae / Aquatic Plants. 1640 mg/l Desmodesmus subspicatus

12.2. Persistence and degradability.**DIPHENYLMETHANE-4,4'-DIISOCYANATE**

Solubility in water. mg/l 0,1 - 100

NOT rapidly biodegradable.

12.3. Bioaccumulative potential.**DIPHENYLMETHANE-4,4'-DIISOCYANATE**

Partition coefficient: n-octanol/water. 4,51

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.**13.1. Waste treatment methods.**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.**14.1. UN number.**

Not applicable.

SECTION 14. Transport information. ... / >>

14.2. UN proper shipping name.

Not applicable.

14.3. Transport hazard class(es).

Not applicable.

14.4. Packing group.

Not applicable.

14.5. Environmental hazards.

Not applicable.

14.6. Special precautions for user.

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso category. None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

Point. 3

Contained substance.

Point.	52	DIISONONYL PHTHALATE
Point.	56	DIPHENYLMETHANE-4,4'-DIISOCYANATE

Reg. no.: 01-2119457014-47-XXXX

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (VwVwS 2005).

WGK 1: Low hazard to waters

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Carc. 2	Carcinogenicity, category 2
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2

SECTION 16. Other information. ... / >>

Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Resp. Sens. 1	Respiratory sensitization, category 1
Skin Sens. 1	Skin sensitization, category 1
H351	Suspected of causing cancer.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
EUH204	Contains isocyanates. May produce an allergic reaction.

Use descriptor system:

ERC 2	Formulation of preparations
ERC 5	Industrial use resulting in inclusion into or onto a matrix
ERC 8b	Wide dispersive indoor use of reactive substances in open systems
PC 1	Adhesives, sealants
PC 21	Laboratory chemicals
PROC 10	Roller application or brushing
PROC 15	Use as laboratory reagent
PROC 3	Use in closed batch process (synthesis or formulation)
PROC 4	Use in batch and other process (synthesis) where opportunity for exposure arises
PROC 5	Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)
PROC 8a	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
PROC 8b	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
PROC 9	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
SU 10	Formulation [mixing] of preparations and/or re-packaging (excluding alloys)
SU 17	General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment
SU 19	Building and construction work

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
2. Regulation (EU) 1272/2008 (CLP) of the European Parliament

SECTION 16. Other information. ... / >>

3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01 / 02 / 09 / 11 / 12 / 15 / 16.