



## SAFETY DATA SHEET BRUSHABLE SEAM SEALER

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name BRUSHABLE SEAM SEALER  
Product No. T3030

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer International Applications Limited  
18 Wildmere Road,  
Wildmere Industrial Estate,  
Banbury, Oxfordshire, OX16 3JU.  
Tel: +44 (0) 1295 274004  
Fax: +44 (0) 1295 211268  
Email: sales@international-applications.com

#### 1.4. Emergency telephone number

+44 (0) 1295 274004

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Liq. 3 - H226
Human health	Acute Tox. 4 - H312; Acute Tox. 4 - H332; Skin Irrit. 2 - H315
Environment	Aquatic Chronic 3 - H412

Classification (1999/45/EEC) Xn; R20/21. Xi; R38. R52/53, R10.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### 2.2. Label elements

Contains XYLENE

Label In Accordance With (EC) No. 1272/2008



Signal Word Warning  
Hazard Statements

H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.

**BRUSHABLE SEAM SEALER**

## Precautionary Statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P273	Avoid release to the environment.
P261	Avoid breathing vapour/spray.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P501	Dispose of contents/container in accordance with local regulations.

## Supplementary Precautionary Statements

P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash contaminated skin thoroughly after handling.
P321	Specific treatment (see medical advice on this label).
P370+378	In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P322	Specific measures (see ... on this label).
P332+313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P403+235	Store in a well-ventilated place. Keep cool.

**2.3. Other hazards****SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures**

STYRENE BUTADIENE RUBBER	10.0 - <20.0%
CAS-No.: 26471-45-4	EC No.:
Classification (EC 1272/2008) Aquatic Chronic 3 - H412	Classification (67/548/EEC) R52/53.

**BRUSHABLE SEAM SEALER**

XYLENE		50.0 - <75.0%
CAS-No.: 1330-20-7	EC No.: 215-535-7	
Classification (EC 1272/2008)	Classification (67/548/EEC)	
Flam. Liq. 3 - H226	R10	
Acute Tox. 4 - H312	Xn;R20/21	
Acute Tox. 4 - H332	Xi;R38	
Skin Irrit. 2 - H315		
ZINC OXIDE		0.5 - < 1.0%
CAS-No.: 1314-13-2	EC No.: 215-222-5	
Classification (EC 1272/2008)	Classification (67/548/EEC)	
Aquatic Acute 1 - H400	N;R50/53	
Aquatic Chronic 1 - H410		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### SECTION 4: FIRST AID MEASURES

##### **4.1. Description of first aid measures**

###### General information

Remove affected person from source of contamination. NOTE! Effects may be delayed. Keep affected person under observation. Get medical attention. CAUTION! First aid personnel must be aware of own risk during rescue! Move the exposed person to fresh air at once. NOTE! Keep affected person away from heat, sparks and flames! Perform artificial respiration if breathing has stopped. Place unconscious person on the side in the recovery position and ensure breathing can take place.

###### Inhalation

Remove victim immediately from source of exposure. Move injured person into fresh air and keep person calm under observation. If uncomfortable: Seek hospital and bring these instructions. Place unconscious person on the side in the recovery position and ensure breathing can take place. Perform artificial respiration if breathing has stopped.

###### Ingestion

Get medical attention immediately! Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and bring along these instructions. Do not give victim anything to drink if he is unconscious. NOTE! Keep affected person away from heat, sparks and flames! When risk of unconsciousness, place and transport the victim in secured side position.

###### Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Rinse with water. Use suitable lotion to moisturise skin. Get medical attention promptly if symptoms occur after washing.

###### Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Do not rub eye. Get medical attention if any discomfort continues.

##### **4.2. Most important symptoms and effects, both acute and delayed**

###### General information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure. NOTE! Effects may be delayed. Keep affected person under observation.

## BRUSHABLE SEAM SEALER

### Inhalation

In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. Vapours may cause headache, fatigue, dizziness and nausea. In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and central nervous system effects.

### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication. May cause chemical burns in mouth and throat. Central nervous system depression. Fumes from the stomach contents may be inhaled resulting in the same symptoms as inhalation.

### Skin contact

Prolonged contact may cause redness, irritation and dry skin.

### Eye contact

Irritation, burning, lachrymation, blurred vision after liquid splash.

### **4.3. Indication of any immediate medical attention and special treatment needed**

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

## SECTION 5: FIREFIGHTING MEASURES

### **5.1. Extinguishing media**

#### Extinguishing media

Use: Foam, carbon dioxide or dry powder. Water. Use fire-extinguishing media appropriate for surrounding materials.

#### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

### **5.2. Special hazards arising from the substance or mixture**

#### Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

#### Unusual Fire & Explosion Hazards

HIGHLY FLAMMABLE! Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground to sources of ignition. May travel considerable distance to source of ignition and flash back.

#### Specific hazards

Vapours may form explosive air mixtures even at room temperature. Vapours are heavier than air and may travel along the floor and in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.

### **5.3. Advice for firefighters**

#### Special Fire Fighting Procedures

Avoid breathing fire vapours. Keep up-wind to avoid fumes. Be aware of risk of fire re-starting, and risk of explosion. Cool containers exposed to flames with water until well after the fire is out. Use water SPRAY only to cool containers! Do not put water on leaked material.

#### Protective equipment for fire-fighters

Leave danger zone immediately.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### **6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective clothing as described in Section 8 of this safety data sheet. In case of inadequate ventilation, use respiratory protection. Take precautionary measures against static discharges. Do not smoke, use open fire or other sources of ignition. Do not breathe vapour. Avoid contact with skin and eyes. In case of spills, beware of slippery floors and surfaces.

### **6.2. Environmental precautions**

**BRUSHABLE SEAM SEALER**

Do not discharge into drains, water courses or onto the ground. Prevent entry into drains. Avoid discharge to the aquatic environment.

**6.3. Methods and material for containment and cleaning up**

For waste disposal, see section 13. Stop leak if possible without risk. Collect with absorbent, non-combustible material into suitable containers. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Provide ventilation and confine spill. Do not allow runoff to sewer. Cover large spillages with alcohol-resistant foam.

**6.4. Reference to other sections**

Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

**SECTION 7: HANDLING AND STORAGE****7.1. Precautions for safe handling**

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Keep away from heat, sparks and open flame. Risk of vapour concentration on the floor and in low-lying areas. Static electricity and formation of sparks must be prevented. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Observe good chemical hygiene practices. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Mechanical ventilation or local exhaust ventilation may be required.

**7.2. Conditions for safe storage, including any incompatibilities**

Keep away from heat, sparks and open flame. Keep containers tightly closed. Keep upright. Keep in original container. Avoid contact with oxidising agents. Do not store near heat sources or expose to high temperatures. Store separated from: Oxidising material.

Storage Class

Flammable liquid storage.

**7.3. Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
XYLENE	WEL	50 ppm	220 mg/m <sup>3</sup>	100 ppm	441 mg/m <sup>3</sup>	Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

**8.2. Exposure controls**

Protective equipment



Process conditions

Provide eyewash station.

**BRUSHABLE SEAM SEALER****Engineering measures**

Provide explosion proof ventilation for high concentrations. Observe occupational exposure limits and minimize the risk of inhalation of vapours. All handling to take place in well-ventilated area.

**Respiratory equipment**

If ventilation is insufficient, suitable respiratory protection must be provided. Check that mask fits tight and change filter regularly. Use respiratory equipment with gas filter, type AX.

**Hand protection**

For prolonged or repeated skin contact use suitable protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.

**Eye protection**

Wear approved, tight fitting safety glasses where splashing is probable.

**Other Protection**

Wear suitable protective clothing as protection against splashing or contamination.

**Hygiene measures**

Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke. Isolate contaminated clothing and wash before reuse.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties**

Appearance	Paste
Colour	Grey.
Odour	Petroleum.
Solubility	Insoluble in water
Initial boiling point and boiling range (°C)	137 760 mm Hg
Melting point (°C)	Not determined.
Relative density	1.32 20°C
Vapour density (air=1)	Not determined.
Vapour pressure	Not determined.
Evaporation rate	Not determined.
Viscosity	>1, 000, 000 cP 20°C
Decomposition temperature (°C)	Not determined.
Odour Threshold, Lower	Not determined.
Odour Threshold, Upper	Not determined.
Flash point (°C)	27 CC (Closed cup).
Auto Ignition Temperature (°C)	Not determined.
Flammability Limit - Lower(%)	1
Flammability Limit - Upper(%)	7
Partition Coefficient (N-Octanol/Water)	Not determined.
Oxidising properties	Not available.

**BRUSHABLE SEAM SEALER****9.2. Other information**

None.

**SECTION 10: STABILITY AND REACTIVITY****10.1. Reactivity**

The product may form explosive vapours/air mixtures even at normal room temperatures.

**10.2. Chemical stability**

Stable under normal temperature conditions and recommended use.

**10.3. Possibility of hazardous reactions**

Not relevant

**10.4. Conditions to avoid**

Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

**10.5. Incompatible materials**

Materials To Avoid  
Strong oxidising substances.

**10.6. Hazardous decomposition products**

None at ambient temperatures. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

Toxic Dose 1 - LD 50  
4300 mg/kg (oral rat)  
Toxic Dose 2 - LD 50  
2119 mg/kg (oral-mouse)  
Toxicological information  
No information available.

**Acute toxicity:**

Xylene

Acute Toxicity (Dermal LD50)  
> 1700 mg/kg Rabbit  
Xylene

**General information**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Contains small amounts of organic solvents. Extensive use of the product in areas with inadequate ventilation may result in hazardous vapour concentrations.

**Inhalation**

Vapours may irritate throat and respiratory system and cause headache, dizziness and dullness. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication.

**BRUSHABLE SEAM SEALER****Ingestion**

May cause internal injury. May cause nausea, headache, dizziness and intoxication. Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

**Skin contact**

Prolonged contact may cause dryness of the skin. Repeated exposure may cause skin dryness or cracking.

**Eye contact**

Irritating and may cause redness and pain. Spray and vapour in the eyes may cause irritation and smarting.

**Health Warnings**

This chemical can be hazardous when inhaled and/or touched. This chemical may cause skin/eye irritation and burns (corrosive). May cause severe internal injury. Vapour from this chemical can be hazardous when inhaled.

**Route of entry**

Inhalation. Ingestion. Skin and/or eye contact. Skin absorption.

**Medical Symptoms**

Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo.

**Medical Considerations**

Risk of chemical pneumonia after aspiration.

**SECTION 12: ECOLOGICAL INFORMATION****Ecotoxicity**

The product contains a substance which has a photochemical ozone creation potential.

**12.1. Toxicity****Acute Fish Toxicity**

Not considered toxic to fish.

LC 50, 96 Hrs, Fish mg/l 13.5

**Acute Toxicity - Fish**

Not available.

**Xylene**

EC 50, 48 Hrs, Daphnia, mg/l 3.82

**Acute Toxicity - Aquatic Invertebrates**

Not available.

**Xylene****12.2. Persistence and degradability****Degradability**

There are no data on the degradability of this product.

**12.3. Bioaccumulative potential****Bioaccumulative potential**

No data available on bioaccumulation.

**Partition coefficient**

Not determined.

**12.4. Mobility in soil****Adsorption/Desorption Coefficient**

Not available.

**12.5. Results of PBT and vPvB assessment**

Not Classified as PBT/vPvB by current EU criteria.



**BRUSHABLE SEAM SEALER****12.6. Other adverse effects**

Not available.

**SECTION 13: DISPOSAL CONSIDERATIONS**

## General information

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority. Do not puncture or incinerate even when empty.

**13.1. Waste treatment methods**

Confirm disposal procedures with environmental engineer and local regulations. Make sure containers are empty before discarding (explosion risk). Empty containers must not be burned because of explosion hazard. Recover and reclaim or recycle, if practical.

**SECTION 14: TRANSPORT INFORMATION****14.1. UN number**

UN No. (ADR/RID/ADN)	1133
UN No. (IMDG)	1133
UN No. (ICAO)	1133

**14.2. UN proper shipping name**

Proper Shipping Name      ADHESIVES

**14.3. Transport hazard class(es)**

ADR/RID/ADN Class	3
ADR/RID/ADN Class	Class 3: Flammable liquids.
ADR Label No.	3
IMDG Class	3
ICAO Class/Division	3
Transport Labels	

**14.4. Packing group**

ADR/RID/ADN Packing group	III
IMDG Packing group	III
ICAO Packing group	III

**14.5. Environmental hazards**

Environmentally Hazardous Substance/Marine Pollutant  
No.

**14.6. Special precautions for user**

EMS                              F-E, S-D

**BRUSHABLE SEAM SEALER**

Emergency Action Code •3Y  
Hazard No. (ADR) 30  
Tunnel Restriction Code (D/E)

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

**SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

## EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**15.2. Chemical Safety Assessment**

No chemical safety assessment has been carried out.

**SECTION 16: OTHER INFORMATION**

## Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision Date 02/05/2014  
Revision 10  
Supersedes date 05/12/2013 v9  
Safety Data Sheet Status Approved.

## Risk Phrases In Full

R10 Flammable  
R20/21 Harmful by inhalation and in contact with skin.  
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R38 Irritating to skin.  
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## Hazard Statements In Full

H315 Causes skin irritation.  
H226 Flammable liquid and vapour.  
H332 Harmful if inhaled.  
H312 Harmful in contact with skin.  
H412 Harmful to aquatic life with long lasting effects.  
H410 Very toxic to aquatic life with long lasting effects.  
H400 Very toxic to aquatic life.