

## 1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: *Etalon Fine Putty***
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
*No further relevant information available.*
- **Application of the substance / the mixture** *Knife filler/ Surfacer*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
*Alexport*  
*Acadimou 111A*  
*P.O.BOX 1008*  
*Thessaloniki-56224, Greece*  
*www.etalon.gr*  
*www.etalon-marine.gr*
- **1.4 Emergency telephone number:** *+30 2310501814*

## 2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

*Flam. Liq. 3 H226 Flammable liquid and vapour.*



GHS08 health hazard

*Repr. 2 H361d Suspected of damaging the unborn child.*

*STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.*



GHS07

*Skin Irrit. 2 H315 Causes skin irritation.*

*Eye Irrit. 2 H319 Causes serious eye irritation.*

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
*The product is classified and labelled according to the CLP regulation.*
- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**  
*styrene*
- **Hazard statements**  
*H226 Flammable liquid and vapour.*  
*H315 Causes skin irritation.*  
*H319 Causes serious eye irritation.*  
*H361d Suspected of damaging the unborn child.*

**Trade name: Etalon Fine Putty**

(Contd. of page 1)

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3 Other hazards****Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

**3 Composition/information on ingredients****3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 100-42-5	styrene	10-≤20%
EINECS: 202-851-5	⚠ Flam. Liq. 3, H226; ⚠ Repr. 2, H361d; STOT RE 1, H372; Asp.	
Reg.nr.: 01-2119457861-32	⚠ Tox. 1, H304; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**4 First aid measures****4.1 Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

**After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** If symptoms persist consult doctor.**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**Information for doctor:****5 Firefighting measures****5.1 Extinguishing media**

· **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

(Contd. on page 3)

**Trade name: Etalon Fine Putty**

(Contd. of page 2)

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

### 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

#### 100-42-5 styrene

WEL	Short-term value: 1080 mg/m <sup>3</sup> , 250 ppm Long-term value: 430 mg/m <sup>3</sup> , 100 ppm
-----	--

- **Additional information:** The lists valid during the making were used as basis.

### 8.2 Exposure controls

- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.

(Contd. on page 4)

**Trade name: Etalon Fine Putty**

(Contd. of page 3)

*Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.*

- **Respiratory protection:**  
Filter A/P2 (EN 141, EN 143)



*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.*

- **Protection of hands:**



*Protective gloves (EN 374)*

- **Material of gloves**  
Fluorocarbon rubber (Viton)  
Recommended thickness of the material:  $\geq 0.7$  mm
- **Breakthrough time of glove material** Value for the permeation: Level  $\leq 6$
- **Eye protection:**



*Tightly sealed goggles*

## 9 Physical and chemical properties

### · 9.1 Information on basic physical and chemical properties

#### · General Information

##### · Appearance:

· <b>Form:</b>	Viscous
· <b>Colour:</b>	White
· <b>Odour:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.

##### · Change in condition

· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Initial boiling point and boiling range:</b>	145 °C

· **Flash point:** 34 °C (DIN 53213)

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 480 °C (DIN 51794)

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

##### · Explosion limits:

· <b>Lower:</b>	1.2 Vol %
· <b>Upper:</b>	8.9 Vol %

· **Vapour pressure at 20 °C:** 6 hPa

(Contd. on page 5)

**Trade name: Etalon Fine Putty**

(Contd. of page 4)

· <b>Density at 20 °C:</b>	1.745 g/cm <sup>3</sup> (DIN 53217)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic at 20 °C:</b>	80.000 mPas
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>VOC (EC)</b>	0.44 %
<b>Solids content (weight-%):</b>	82.8 %
· <b>9.2 Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

## 11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

### · LD/LC50 values relevant for classification:

#### 100-42-5 styrene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rat)
Inhalative	LC50/4 h (Dämpfe)	11.8 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**  
Suspected of damaging the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**  
Causes damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 6)

**Trade name: Etalon Fine Putty**

· **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. of page 5)

## 12 Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) : hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

## 13 Disposal considerations


- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
-----------	---

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- |   |                            |
|---|----------------------------|
| · <b>14.1 UN-Number</b>   | UN3269                     |
| · <b>ADR, IMDG, IATA</b>  |                            |
| · <b>14.2 UN proper shipping name</b>   | UN3269 POLYESTER RESIN KIT |
| · <b>ADR</b>  | POLYESTER RESIN KIT        |
| · <b>IMDG, IATA</b>   |                            |
| · <b>14.3 Transport hazard class(es)</b>  |                            |
| · <b>ADR</b>  |                            |
|  |                            |
| · <b>Class</b>  | 3 (F3) Flammable liquids.  |
| · <b>Label</b>  | 3                          |

(Contd. on page 7)

**Trade name: Etalon Fine Putty**

(Contd. of page 6)

· **IMDG, IATA**



· **Class** 3 Flammable liquids.  
· **Label** 3

· **14.4 Packing group**  
· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**  
· **Marine pollutant:** No

· **14.6 Special precautions for user** Warning: Flammable liquids.  
· **Danger code (Kemler):** -  
· **EMS Number:** F-E,S-D  
· **Stowage Category** A

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**  
· **Transport category** 3  
· **Tunnel restriction code** E

· **IMDG**  
· **Limited quantities (LQ)** 5L

· **UN "Model Regulation":** UN 3269 POLYESTER RESIN KIT, 3, III

**15 Regulatory information**

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· **National regulations:**

Class	Share in %
NK	10-25

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.

(Contd. on page 8)

**Trade name: Etalon Fine Putty**

(Contd. of page 7)

*H319 Causes serious eye irritation.**H332 Harmful if inhaled.**H335 May cause respiratory irritation.**H361d Suspected of damaging the unborn child.**H372 Causes damage to the hearing organs through prolonged or repeated exposure.**H412 Harmful to aquatic life with long lasting effects.*

· **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Flam. Liq. 3: Flammable liquids – Category 3*

*Acute Tox. 4: Acute toxicity – Category 4*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*Repr. 2: Reproductive toxicity – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1*

*Asp. Tox. 1: Aspiration hazard – Category 1*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

· **\* Data compared to the previous version altered.**