

# SAFETY DATA SHEET GUN WASH

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name GUN WASH

Internal identification TGW

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** PC9a: Coatings and paints, thinners, paint removers.

### 1.3. Details of the supplier of the safety data sheet

Supplier International Applications Limited

18 Wildmere Road

Wildmere Industrial Estate

Banbury Oxfordshire OX16 3JU

Tel: +44 (0) 1295 274004 Fax: +44 (0) 1295 211268

Email: sales@international-applications.com

## 1.4. Emergency telephone number

Emergency telephone Tel: +44 (0) 1295 274004 (8.30AM - 5.30PM)

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

## Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361fd STOT SE 3 - H336 STOT RE 2 - H373

Asp. Tox. 1 - H304

**Environmental hazards** Aquatic Chronic 2 - H411

## 2.2. Label elements

### **Pictogram**









Signal word

Danger

Hazard statements H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements** P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof electrical equipment.

P260 Do not breathe vapour/ spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P308+P313 IF exposed or concerned: Get medical advice/ attention.

P233 Keep container tightly closed.

Contains TOLUENE, HEPTANE, CYCLOHEXANE, HEXANE-norm, METHANOL, PROPAN-1-OL,

PROPAN-2-OL, BUTANOL-norm, BUTAN-2-OL, TETRAHYDROFURAN, ACETONE, BUTANONE, METHYL ACETATE, ETHYL ACETATE, PROPYL ACETATE, BUTYL

ACETATE -norm

Supplementary precautionary

statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P240 Ground/ bond container and receiving equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/ shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P314 Get medical advice/ attention if you feel unwell.

P331 Do NOT induce vomiting.

P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations.

#### 2.3. Other hazards

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

TOLUENE		5-10%
CAS number: 108-88-3	EC number: 203-625-9	REACH registration number: 01- 2119471310-51-XXXX
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F;R11 Rep	r. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67
Skin Irrit. 2 - H315		
Repr. 2 - H361d		
STOT SE 3 - H336		
STOT RE 2 - H373		
Asp. Tox. 1 - H304		

BUTYL ACETATE -norm		<5	;%
CAS number: 123-86-4	EC number: 204-658-1	REACH registration number: 01-2119485493-29-XXXX	
Classification	Classificatio	n (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 R66 R6	37	
STOT SE 3 - H336			

ACETONE		<5	;%
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01- 2119471330-49-XXXX	
Classification	Classificati	on (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F;R11 Xi;R36 R66 R67		
Eye Irrit. 2 - H319			
STOT SE 3 - H336			

METHANOL		</th <th>5%</th>	5%
CAS number: 67-56-1	EC number: 200-659-6	REACH registration number: 01- 2119433307-44-XXXX	
Classification	Classification	on (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F;R11 T;R2	23/24/25,R39/23/24/25	
Acute Tox. 3 - H301			
Acute Tox. 3 - H311			
Acute Tox. 3 - H331			
STOT SE 1 - H370			

TETRAHYDROFURAN			<5%
CAS number: 109-99-9	EC number: 203-726-8	REACH registration number: 01-2119444314-46-XXXX	
Classification	Classification (67/548/EEC or 1999/45/EC)		
Flam. Liq. 2 - H225	Carc. Cat. 3;R40. Xi;R36/37. F;R11. R19.		
Eye Irrit. 2 - H319			
Carc. 2 - H351			

 PROPAN-1-OL
 <5%</th>

 CAS number: 71-23-8
 EC number: 200-746-9
 REACH registration number: 01-2119486761-29-XXXX

 Classification
 Classification (67/548/EEC or 1999/45/EC)

 Flam. Liq. 2 - H225
 F;R11 Xi;R41 R67

 Eye Dam. 1 - H318
 STOT SE 3 - H336

 METHYL ACETATE
 <5%</th>

 CAS number: 79-20-9
 EC number: 201-185-2
 REACH registration number: 01-2119459211-47-XXXX

 Classification
 Classification (67/548/EEC or 1999/45/EC)

 Flam. Liq. 2 - H225
 F;R11 Xi;R36 R66 R67

 Eye Irrit. 2 - H319
 STOT SE 3 - H336

XYLENE

CAS number: 1330-20-7

EC number: 215-535-7

REACH registration number: 012119488216-32-XXXX

Classification

Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 3 - H226

Acute Tox. 4 - H312

Acute Tox. 4 - H332

Skin Irrit. 2 - H315

**HEPTANE** <5% CAS number: 142-82-5 EC number: 205-563-8 REACH registration number: 01-2119457603-38-XXXX M factor (Acute) = 1 M factor (Chronic) = 1 Classification (67/548/EEC or 1999/45/EC) Classification Flam. Liq. 2 - H225 F;R11 Xn;R65 Xi;R38 R67 N;R50/53

Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

**ETHYLBENZENE** <5%

CAS number: 100-41-4 EC number: 202-849-4

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11 Xn;R20

Acute Tox. 4 - H332

**CYCLOHEXANE** <5%

CAS number: 110-82-7 EC number: 203-806-2 REACH registration number: 01-

2119463273-41-XXXX

M factor (Acute) = 1 M factor (Chronic) = 1

Classification Classification (67/548/EEC or 1999/45/EC) Flam. Liq. 2 - H225

Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

STOT SE 3 - H336

F;R11 Xn;R65 Xi;R38 R67 N;R50/53

**PROPYL ACETATE** <5%

CAS number: 109-60-4 EC number: 203-686-1 REACH registration number: 01-

2119484620-39-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11 Xi;R36 R66 R67 Eye Irrit. 2 - H319

5/28

<5% ISOBUTYL METHYL KETONE (MIBK)

CAS number: 108-10-1 EC number: 203-550-1 REACH registration number: 01-

2119473980-30-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11 Xn;R20 Xi;R36/37 R66

Acute Tox. 4 - H332 Eye Irrit. 2 - H319 STOT SE 3 - H335

**ETHYL ACETATE** <5%

CAS number: 141-78-6 EC number: 205-500-4 REACH registration number: 01-

2119475103-46-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11 Xi;R36 R66 R67

Eye Irrit. 2 - H319 STOT SE 3 - H336

PROPAN-2-OL <5%

CAS number: 67-63-0 EC number: 200-661-7 REACH registration number: 01-

2119457558-25-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11 Xi;R36 R67

Eye Irrit. 2 - H319 STOT SE 3 - H336

**HEXANE-norm** <5%

CAS number: 110-54-3 EC number: 203-777-6 REACH registration number: TB252081-

55 Pre-Registration Number

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11 Repr. Cat. 3;R62 Xn;R48/20,R65 Xi;R38 R67

Skin Irrit. 2 - H315

Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

N:R51/53

**BUTAN-2-OL** <5%

CAS number: 78-92-2 EC number: 201-158-5

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 3 - H226 R10 Xi:R36/37 R67

Eye Irrit. 2 - H319

STOT SE 3 - H335, H336

## **GUN WASH**

BUTANOL-norm <5%

CAS number: 71-36-3 EC number: 200-751-6 REACH registration number: 01-

2119484630-38-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 3 - H226 R10 Xn;R22 Xi;R37/38,R41 R67

Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335, H336

ETHANOL <5%

CAS number: 64-17-5 EC number: 200-578-6

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### SECTION 4: First aid measures

## 4.1. Description of first aid measures

Inhalation Remove casualty from exposure ensuring one's own safety whilst doing so. If inhaled remove

person to fresh air and keep comfortable for breathing.

**Ingestion** Do not induce vomiting. If conscious give 500ml of water to drink immediatley. wash out

mouth with water. Consult a doctor.

Skin contact Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash skin

thoroughly with soap and water. If irritation occurs get medical advice/attention.

Eye contact If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Transfer to hospital for specialist examination.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Inhalation** There may be irritation of the throat with a feeling of tightness in the chest.

**Ingestion** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may

occur.

**Skin contact** There may be irritation and redness at the site of contact.

**Eye contact** There may be pain and redness. The eyes may water profusely. There may be severe pain.

The vision may become blurred. May cause permanent damage.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Specific treatments** Eye bathing equipment should be available on the premises.

### SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire. Water Spray may be used to

keep fire exposed containers cool

## 5.2. Special hazards arising from the substance or mixture

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Toxic

gases or vapours.

5.3. Advice for firefighters

Personal precautions

Special protective equipment for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact with skin

and eyes.

### SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

\_\_\_\_\_\_

Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid. Take precautionary measures

against static discharge.

### 6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Contain the spillage using

bunding. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal

by an appropriate method. Use only non-sparking tools.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8.

### SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation of mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting. Do not breathe mist/vapours/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep container tightly closed. Use only

non-sparking tools.

Advice on general occupational hygiene

Take off contaminated clothing and wash it before re-use.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) No data available.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

### **TOLUENE**

Long-term exposure limit (8-hour TWA):  $mg/m3(Sk) \ ppm(Sk) \ 1 \ mg/m3(Sk)$ Short-term exposure limit (15-minute):  $mg/m3(Sk) \ \ 0 \ ppm(Sk) \ 4 \ mg/m3(Sk)$ 

### **BUTYL ACETATE -norm**

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m<sup>3</sup>

#### **ACETONE**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

#### **METHANOL**

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 266 mg/m3(Sk) Short-term exposure limit (15-minute): WEL 250 ppm(Sk) 333 mg/m3(Sk)

### **TETRAHYDROFURAN**

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 150 mg/m3(Sk) Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 300 mg/m3(Sk)

#### **PROPAN-1-OL**

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 500 mg/m3(Sk) Short-term exposure limit (15-minute): WEL 250 ppm(Sk) 625 mg/m3(Sk)

#### **METHYL ACETATE**

Long-term exposure limit (8-hour TWA): WEL 200 ppm 616 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 250 ppm 770 mg/m<sup>3</sup>

#### **XYLENE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m3(Sk) Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m3(Sk)

#### **BUTANONE**

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 600 mg/m3(Sk) Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 899 mg/m3(Sk)

### **HEPTANE**

Long-term exposure limit (8-hour TWA): WEL 500 ppm Short-term exposure limit (15-minute): WEL

### **ETHYLBENZENE**

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 441 mg/m3(Sk) Short-term exposure limit (15-minute): WEL 125 ppm(Sk) 552 mg/m3(Sk)

#### **CYCLOHEXANE**

Long-term exposure limit (8-hour TWA): WEL 100 ppm 350 mg/m³ Short-term exposure limit (15-minute): WEL 300 ppm 1050 mg/m³

#### PROPYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm 849 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 250 ppm 1060 mg/m<sup>3</sup>

#### ISOBUTYL METHYL KETONE (MIBK)

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 208 mg/m3(Sk) Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 416 mg/m3(Sk)

#### **ETHYL ACETATE**

Long-term exposure limit (8-hour TWA): WEL 200 ppm Short-term exposure limit (15-minute): WEL 400 ppm

### PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m<sup>3</sup>

### **HEXANE-norm**

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL

#### **BUTAN-2-OL**

Long-term exposure limit (8-hour TWA): WEL 100 ppm 308 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 150 ppm 462 mg/m<sup>3</sup>

#### **BUTANOL-norm**

Long-term exposure limit (8-hour TWA): WEL

Short-term exposure limit (15-minute): WEL 50 ppm(Sk) 154 mg/m3(Sk)

### **ETHANOL**

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit

DNEL No data available.PNEC No data available.

### 8.2. Exposure controls

Protective equipment

Appropriate engineering

Ensure there is sufficient ventilation of the area. Use explosion-proof

controls electrical/ventilating/lighting. Take precautionary measures against static discharge.

**Eye/face protection** Tightly fitting safety goggles. Ensure eye bath is to hand.

Hand protection Wear protective gloves.

Other skin and body

protection

Wear protective clothing. Take precautionary measures against static discharge.

**Respiratory protection** Self-contained breathing apparatus must be available in case of emergency.

Environmental exposure

controls

Prevent from entering in public sewers or the immediate environment.

### **SECTION 9: Physical and Chemical Properties**

## 9.1. Information on basic physical and chemical properties

Appearance Coloured liquid.

Odour Unpleasant.

Odour threshold Data lacking.

pH Data lacking.

Melting point Data lacking.

Initial boiling point and range 55 - 160°C @ 760 mm Hg

Flash point < 21°C

**Evaporation rate** Data lacking.

**Evaporation factor** Data lacking.

Flammability (solid, gas) Data lacking.

Upper/lower flammability or

explosive limits

Data lacking.

## **GUN WASH**

Other flammability Data lacking.

Vapour pressure <110 kPa @ 20°C

Vapour density Data lacking.

Relative density 0.8 - 0.9 @ 20°C

Bulk density Data lacking.

Solubility(ies) Data lacking.

Partition coefficient Data lacking.

Auto-ignition temperature >203°C

**Decomposition Temperature** Data lacking.

Viscosity Non-viscous

**Explosive properties** Data lacking.

Explosive under the influence

\_\_\_\_\_

Not considered to be explosive.

of a flame

Oxidising properties Not available.

9.2. Other information

Other information Not available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** Stable under recommended transport or storage conditions.

10.2. Chemical stability

**Stability** Stable at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous** Under normal conditions of storage and use, no hazardous reactions will occur.

**reactions** Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid Avoid heat.

10.5. Incompatible materials

Materials to avoid Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition In combustion emits toxic fumes.

products

### SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity - dermal

**ATE dermal (mg/kg)** 4,810.5

**Inhalation** There may be irritation of the throat with a feeling of tightness in the chest.

**Ingestion** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may

occur.

**Skin contact** There may be irritation or redness at the site of contact.

**Eye contact** There may be pain and redness. The eyes may water profusely. There may be severe pain.

The vision may become blurred. May cause permanent damage.

### Toxicological information on ingredients.

### **TOLUENE**

**Toxicological effects** This product is toxic.

Inhalation Harmful if inhaled

**Ingestion** Very toxic if swallowed.

**Skin contact** May be harmful if absorbed through the skin.

**Eye contact** Risk of serious damage to eyes.

Acute and chronic health

hazards

May cause damage to the liver and kidneys.

Route of entry Inhalation Ingestion. Skin and/or eye contact

Target organs Liver Kidneys Respiratory system, lungs Central nervous system

Medical symptoms Difficulty in breathing. Drowsiness, dizziness, disorientation, vertigo.

Unconsciousness, possibly death.

**Medical considerations** Pre Existing Respiratory Disorders and Lung Diseases.

### **BUTYL ACETATE -norm**

**Inhalation** Drowsiness, discrientation, vertigo.

**Skin contact** Prolonged contact may cause dryness of the skin.

Eye contact Irritating to eyes.

Acute and chronic health

hazards

Gas or vapour in high concentrations may irritate the respiratory system.

Route of entry Inhalation Skin absorption Ingestion.

**Medical symptoms** Irritation of eyes and mucous membranes.

### **ACETONE**

### **GUN WASH**

Acute and chronic health hazards

Gas or vapour is harmful on prolonged exposure or in high concentrations. Symptoms following overexposure may include the following: Irritation of eyes and mucous membranes. Narcotic effect. A single exposure may cause the following adverse effects: Central nervous system depression. Vapour from this product may be hazardous by inhalation. Repeated exposure may cause chronic eye irritation. Defatting, drying and cracking of skin. Swallowing concentrated chemical may cause severe internal injury. Central and/or peripheral nervous system damage. Prolonged or repeated exposure may cause the following adverse effects: Serious damage to the lining of nose, throat and lungs. Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Sore throat. Irritation of nose, throat and airway.

Route of entry Inhalation Skin absorption Ingestion. Skin and/or eye contact

Target organs Central nervous system Eyes Gastro-intestinal tract Respiratory system, lungs Skin

Medical symptoms Irritation of eyes and mucous membranes. Rhinitis (inflammation of the nasal

mucous membranes). Upper respiratory irritation. General respiratory distress, unproductive cough. Skin irritation. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Intoxication. Symptoms following overexposure to dust may include the following: Irritability. Headache.

Nausea, vomiting. Hypotension (low blood pressure).

Medical considerations Skin disorders and allergies.

## **METHANOL**

Acute and chronic health

hazards

Gas or vapour is harmful on prolonged exposure or in high concentrations. This product is corrosive. This product may cause skin and eye irritation. Prolonged contact may cause burns. Toxic through skin absorption (percutaneous). Narcotic effect. Repeated exposure may cause chronic eye irritation. May cause chemical eye burns. Acute eczematous dermatitis, contact type erythema, oedema, papules, vesicles, bullae, crusts, desquamation. Swallowing concentrated chemical may cause severe internal injury.

Route of entry Inhalation Ingestion. Skin and/or eye contact

Target organs Central nervous system Eyes Gastro-intestinal tract Heart & cardiovascular system

Skin

**Medical symptoms** Severe irritation, burning and tearing. Visual disturbances, including blurred vision.

Respiratory failure. Death. Severe skin irritation. Nausea, vomiting. Headache.

Behavioural changes. Tremors, convulsions.

**Medical considerations** Skin disorders and allergies.

### **TETRAHYDROFURAN**

Acute and chronic health

hazards

Gas or vapour is harmful on prolonged exposure or in high concentrations.

Symptoms following overexposure may include the following: Irritation of eyes and mucous membranes. Toxic through skin absorption (percutaneous). Narcotic effect. A single exposure may cause the following adverse effects: Central nervous system depression. Unconsciousness. Death.

Route of entry No route of entry noted.

### **GUN WASH**

Target organs Central nervous system Eyes Kidneys Liver Respiratory system, lungs Skin

Medical symptoms Irritation of eyes and mucous membranes. Dilated pupils. Rhinitis (inflammation of

the nasal mucous membranes). Upper respiratory irritation. General respiratory distress, unproductive cough. Respiratory failure. Death. Skin irritation. Nausea, vomiting. Unconsciousness, possibly death. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Behavioural changes. Hypotension

(low blood pressure). Dizziness.

**Medical considerations** Convulsions. Central nervous system depression.

PROPAN-1-OL

**Toxicological effects** No evidence of carcinogenic mutagenic or teratogenic effects

METHYL ACETATE

Inhalation Vapour may irritate respiratory system/lungs. Vapours may irritate throat/respiratory

system. Symptoms following overexposure may include the following: Headache.

Dizziness. Drowsiness. May cause an asthma-like shortness of breath.

Ingestion May cause stomach pain or vomiting. Pneumonia may be the result if vomited

material containing solvents reaches the lungs.

**Skin contact** Product has a defatting effect on skin.

**Eye contact** Severe irritation, burning and tearing.

Acute and chronic health

hazards

This product may cause skin and eye irritation. Prolonged inhalation of high concentrations may damage respiratory system. Product has a defatting effect on skin. May cause allergic contact eczema. Prolonged and repeated contact with

solvents over a long period may lead to permanent health problems.

Route of entry Inhalation Skin absorption Ingestion.

Target organs Central nervous system Eyes Respiratory system, lungs

**Medical symptoms** Severe irritation, burning and tearing. Gas or vapour in high concentrations may

irritate the respiratory system. Symptoms following overexposure may include the

following: Headache. Fatigue. Nausea, vomiting.

**Medical considerations** Pre-existing eye problems. Pre Existing Respiratory Disorders and Lung Diseases.

**XYLENE** 

Acute and chronic health

hazards

This product is corrosive. This product may cause skin and eye irritation. Prolonged contact may cause burns. Symptoms following overexposure may include the following: Irritation of eyes and mucous membranes. Toxic through skin absorption (percutaneous). A single exposure may cause the following adverse effects: Central nervous system depression. Anaesthetic in high concentrations. Repeated

exposure may cause chronic eye irritation. May cause chemical eye burns. Acute eczematous dermatitis, contact type erythema, oedema, papules, vesicles, bullae, crusts, desquamation. Swallowing concentrated chemical may cause severe

internal injury. Unconsciousness. Death.

Route of entry Inhalation Skin absorption Ingestion. Skin and/or eye contact

### **GUN WASH**

Target organs Blood Central nervous system Eyes Gastro-intestinal tract Kidneys Liver

Respiratory system, lungs Skin

Medical symptoms Severe irritation, burning and tearing. Dilated pupils. Rhinitis (inflammation of the

nasal mucous membranes). Upper respiratory irritation. General respiratory distress, unproductive cough. May cause suffocation. Severe skin irritation. Nausea, vomiting. Unconsciousness, possibly death. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Behavioural changes.

Hypotension (low blood pressure). Dizziness.

**Medical considerations** Skin disorders and allergies. Convulsions. Central nervous system depression.

**BUTANONE** 

**Inhalation** Vapour from this product may be hazardous by inhalation.

**Ingestion** May cause severe internal injury.

Skin contact Product has a defatting effect on skin. May cause allergic contact eczema.

**Eye contact** May cause severe eye irritation.

Route of entry Inhalation Ingestion. Skin absorption Skin and/or eye contact

Medical symptoms Gas or vapour in high concentrations may irritate the respiratory system. Symptoms

following overexposure may include the following: Headache. Fatigue. Nausea,

vomiting. Unconsciousness.

**Medical considerations** Chronic respiratory and obstructive airway diseases. Pre-existing eye problems.

Skin disorders and allergies.

**HEPTANE** 

**Inhalation** Central nervous system depression.

**Ingestion** May cause internal injury.

Skin contact Product has a defatting effect on skin. May cause allergic contact eczema. Product

has a defatting effect on skin.

**Eye contact** Irritating to eyes.

Acute and chronic health

hazards

 $\label{prolonged} \mbox{Prolonged inhalation of high concentrations may damage respiratory system.}$ 

Product has a defatting effect on skin. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Prolonged or repeated exposure to vapours in high concentrations may cause the following

adverse effects: Nausea, vomiting. Headache.

Route of entry Inhalation Ingestion. Skin and/or eye contact

Target organs Central nervous system

Medical symptoms Irritation of eyes and mucous membranes. Skin irritation. Difficulty in breathing.

**ETHYLBENZENE** 

**Toxicological effects** No evidence of carcinogenic mutagenic or teratogenic effects

### **GUN WASH**

### **CYCLOHEXANE**

**Toxicological effects** No evidence of carcinogenic mutagenic or teratogenic effects

Acute and chronic health

hazards

Gas or vapour is toxic or extremely irritating, even on brief exposure. Gas or vapour is harmful on prolonged exposure or in high concentrations. This product is corrosive. This product may cause skin and eye irritation. Prolonged contact may cause burns. Symptoms following overexposure may include the following: Irritation of eyes and mucous membranes. Toxic through skin absorption (percutaneous). Narcotic effect. A single exposure may cause the following adverse effects: Central nervous system depression. Repeated exposure may cause chronic eye irritation. Acute eczematous dermatitis, contact type erythema, oedema, papules, vesicles, bullae, crusts, desquamation. Swallowing concentrated chemical may cause severe

internal injury. Unconsciousness. Death.

Route of entry Inhalation Ingestion. Skin and/or eye contact

Target organs Central nervous system Eyes Respiratory system, lungs Skin

Medical symptoms Severe irritation, burning and tearing. Dilated pupils. Rhinitis (inflammation of the

nasal mucous membranes). Upper respiratory irritation. General respiratory distress, unproductive cough. May cause suffocation. Severe skin irritation. Nausea, vomiting. Unconsciousness, possibly death. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Behavioural changes.

Hypotension (low blood pressure). Dizziness.

**Medical considerations** Skin disorders and allergies. Convulsions. Central nervous system depression.

PROPYL ACETATE

**Toxicological effects** No evidence of carcinogenic mutagenic or teratogenic effects

ISOBUTYL METHYL KETONE (MIBK)

**Toxicological effects** No evidence of carcinogenic mutagenic or teratogenic effects

Acute and chronic health hazards

Gas or vapour is harmful on prolonged exposure or in high concentrations. This product is corrosive. This product may cause skin and eye irritation. Prolonged contact may cause burns. Symptoms following overexposure may include the following: Irritation of eyes and mucous membranes. Toxic through skin absorption (percutaneous). Narcotic effect. A single exposure may cause the following adverse effects: Central nervous system depression. Repeated exposure may cause chronic eye irritation. Acute eczematous dermatitis, contact type erythema, oedema,

papules, vesicles, bullae, crusts, desquamation. Swallowing concentrated chemical

may cause severe internal injury. Unconsciousness. Death.

Route of entry Inhalation Ingestion. Skin and/or eye contact

Target organs Central nervous system Eyes Respiratory system, lungs Skin

### **GUN WASH**

Medical symptoms Severe irritation, burning and tearing. Dilated pupils. Rhinitis (inflammation of the

nasal mucous membranes). Upper respiratory irritation. General respiratory distress, unproductive cough. May cause suffocation. Severe skin irritation. Nausea, vomiting. Unconsciousness, possibly death. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Behavioural changes.

Hypotension (low blood pressure). Dizziness.

**Medical considerations** Skin disorders and allergies. Convulsions. Central nervous system depression.

### **ETHYL ACETATE**

**General information** Prolonged and repeated contact with solvents over a long period may lead to

permanent health problems.

**Inhalation** Vapours may irritate throat/respiratory system. A single exposure may cause the

following adverse effects: Coughing. Difficulty in breathing. May cause damage to mucous membranes in nose, throat, lungs and bronchial system. Excessive inhalation of vapours can cause respiratory irritation, headache, drowsiness and

fatigue.

Ingestion Ingestion may cause severe irritation of the mouth, the oesophagus and the

gastrointestinal tract.

**Skin contact** Product has a defatting effect on skin. Irritating to skin.

**Eye contact** Irritating to eyes.

Acute and chronic health

hazards

Irritating to skin. Irritating to eyes. May cause respiratory system irritation. May

cause severe internal injury. May cause damage to the liver and kidneys.

**Route of entry** Inhalation Skin absorption Ingestion. Skin and/or eye contact

Target organs Liver Kidneys Mucous membranes Gastro-intestinal tract

Medical symptoms Gas or vapour in high concentrations may irritate the respiratory system. Symptoms

following overexposure may include the following: Headache. Fatigue. Nausea, vomiting. Difficulty in breathing. Gastrointestinal symptoms, including upset

stomach. Severe headache. Unconsciousness.

Medical considerations Liver and/or kidney damage. Skin disorders and allergies. Pre-existing eye

problems.

## PROPAN-2-OL

Other health effects Consolidated carcinogen list.

Inhalation Vapours in high concentrations are anaesthetic. Symptoms following overexposure

may include the following: Headache. Fatigue. Dizziness. Central nervous system

depression.

Ingestion Swallowing concentrated chemical may cause severe internal injury.

Skin contact Contains components which may penetrate the skin. Prolonged contact may cause

redness, irritation and dry skin.

**Eye contact** Irritation of eyes and mucous membranes.

### **GUN WASH**

Acute and chronic health

hazards

Exposure; This chemical has good warning properties. Gas or vapour is harmful on prolonged exposure or in high concentrations. Symptoms following overexposure may include the following: Irritation of eyes and mucous membranes. Toxic through skin absorption (percutaneous). Narcotic effect. A single exposure may cause the following adverse effects: Central nervous system depression. May cause chemical eye burns. Swallowing concentrated chemical may cause severe internal injury.

Unconsciousness. Death.

Route of entry Inhalation Ingestion. Skin and/or eye contact

Target organs Central nervous system Eyes Respiratory system, lungs Skin

Medical symptoms Irritation of eyes and mucous membranes. Dilated pupils. Rhinitis (inflammation of

the nasal mucous membranes). Upper respiratory irritation. General respiratory distress, unproductive cough. May cause suffocation. Skin irritation. Nausea, vomiting. Unconsciousness, possibly death. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Behavioural changes. Hypotension

(low blood pressure). Dizziness.

**Medical considerations** Convulsions. Central nervous system depression.

### **HEXANE-norm**

Inhalation Vapours may irritate throat/respiratory system. A single exposure may cause the

following adverse effects: Coughing. Difficulty in breathing. Vapours in high

concentrations are anaesthetic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Central nervous system depression.

**Ingestion** Harmful: possible risk of irreversible effects if swallowed.

**Skin contact** Product has a defatting effect on skin. May cause allergic contact eczema.

**Eye contact** May cause severe eye irritation.

Acute and chronic health

hazards

May cause unconsciousness, blindness and possibly death.

Route of entry Inhalation Ingestion.

Target organs Central nervous system Eyes

Medical symptoms Irritation of eyes and mucous membranes. Unconsciousness.

### **BUTANOL-norm**

Ingestion May cause discomfort if swallowed.

**Skin contact** Product has a defatting effect on skin. May cause allergic contact eczema.

**Eve contact** May cause severe eye irritation.

Acute and chronic health

hazards

Symptoms following overexposure may include the following: Irritation of eyes and

mucous membranes. Gas or vapour in high concentrations may irritate the

respiratory system.

Route of entry Inhalation Ingestion. Skin and/or eye contact

Target organs Eyes Mucous membranes Respiratory system, lungs

### **GUN WASH**

**Medical symptoms** Irritation of eyes and mucous membranes. Drowsiness, diszriness, disorientation,

vertigo.

**Medical considerations** Splash in eye requires examination by eye specialist.

### **ETHANOL**

**Ingestion** May cause liver and/or renal damage.

Skin contact Skin irritation should not occur when used as recommended.

**Eye contact** Irritating to eyes.

Acute and chronic health

hazards

Gas or vapour is harmful on prolonged exposure or in high concentrations.

Symptoms following overexposure may include the following: Irritation of eyes and mucous membranes. Toxic through skin absorption (percutaneous). Narcotic effect. Known or suspected teratogen. A single exposure may cause the following adverse effects: Central nervous system depression. Repeated exposure may cause chronic eye irritation. High concentrations may cause severe lung damage. Defatting, drying and cracking of skin. Swallowing concentrated chemical may cause severe

internal injury. Unconsciousness. Death.

Route of entry Inhalation Ingestion. Skin and/or eye contact

Target organs Central nervous system Eyes Gastro-intestinal tract Liver Respiratory system, lungs

Skin

Medical symptoms Irritation of eyes and mucous membranes. Dilated pupils. Rhinitis (inflammation of

the nasal mucous membranes). Upper respiratory irritation. General respiratory distress, unproductive cough. May cause suffocation. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Headache. Behavioural changes. Hypotension (low blood pressure). Dizziness.

Confusion, agitation and/or excitation.

Medical considerations Convulsions. Central nervous system depression.

### SECTION 12: Ecological Information

## Ecological information on ingredients.

### **ACETONE**

**Ecotoxicity** Fish: Low Daphnia: Moderate

**HEPTANE** 

**Ecotoxicity**The product contains a substance which is toxic to aquatic organisms and which

may cause long-term adverse effects in the aquatic environment.

**ETHYLBENZENE** 

**Ecotoxicity**The product contains a substance which is harmful to aquatic organisms and which

may cause long-term adverse effects in the aquatic environment.

PROPYL ACETATE

**Ecotoxicity** There are no data on the ecotoxicity of this product.

## **GUN WASH**

### ETHYL ACETATE

**Ecotoxicity** The product is not expected to be toxic to aquatic organisms.

**ETHANOL** 

Ecotoxicity The Environmental hazards of this material has not been assessed. Standard

handling protocols apply to prevent release to the environment.

12.1. Toxicity

Ecological information on ingredients.

**TOLUENE** 

Toxicity LOW

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 10 - 100 mg/l, Algae

**BUTYL ACETATE -norm** 

**Toxicity** LOW

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 100 mg/l, Algae

Acute toxicity - aquatic

invertebrates

EC<sub>50</sub>, 48 hours: 44-205 mg/l, Daphnia magna

**ACETONE** 

**Toxicity** LOW

**METHANOL** 

Toxicity LOW

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 24900 mg/l, Algae

**TETRAHYDROFURAN** 

**Toxicity** LOW

**Acute toxicity - fish** Peces LC₅o, 96 horas: 2160 mg/l, Peces

PROPAN-1-OL

**Toxicity** LOW

Acute toxicity - fish LC50, 96 hours: >100 mg/l, Algae

METHYL ACETATE

**Toxicity** Not considered toxic to fish.

Acute toxicity - fish LC<sub>50</sub>, 96 hours: >100 mg/l, Algae

**XYLENE** 

## **GUN WASH**

Toxicity MODERATE.

**BUTANONE** 

**Toxicity** LOW

Acute toxicity - fish LC<sub>50</sub>, 96 hours: >100 mg/l, Algae

**HEPTANE** 

**Toxicity** LOW

Acute aquatic toxicity

**LE(C)**<sub>50</sub>  $0.1 < L(E)C50 \le 1$ 

M factor (Acute) 1

Acute toxicity - fish LC₅₀, 96 hours: 4 mg/l, Algae

Chronic aquatic toxicity

M factor (Chronic) 1

**ETHYLBENZENE** 

Toxicity MODERATE.

**CYCLOHEXANE** 

Toxicity MODERATE.

Acute aquatic toxicity

**LE(C)**<sub>50</sub>  $0.1 < L(E)C50 \le 1$ 

M factor (Acute) 1

Acute toxicity - fish LC₅o, 96 hours: 10-100 mg/l, Algae

Chronic aquatic toxicity

M factor (Chronic) 1

PROPYL ACETATE

**Toxicity** LOW

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours: 318 mg/l, Daphnia magna

ISOBUTYL METHYL KETONE (MIBK)

Acute toxicity - fish LC<sub>50</sub>, 96 hours: >100 mg/l, Algae

PROPAN-2-OL

Toxicity LOW

Acute toxicity - fish LC<sub>50</sub>, 96 hours: >100 mg/l, Algae

## **GUN WASH**

### **HEXANE-norm**

Acute toxicity - fish LC50, 96 hours: Nol Information Found mg/l, Algae

**BUTANOL-norm** 

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 1000-1200 mg/l, Algae

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours: 1855 mg/l, Daphnia magna

**ETHANOL** 

**Toxicity** MODERATE.

Acute toxicity - fish LC<sub>50</sub>, 96 hours: >100 mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability The product is biodegradable.

Ecological information on ingredients.

### **TOLUENE**

Persistence and degradability

MODERATE IN WATER

### **BUTYL ACETATE -norm**

Persistence and degradability

The degradability of the product is not known.

## **ACETONE**

Persistence and degradability

Significant Conpartments likely to be air, water. Persistance: in air, moderate; in water and soil, rapid biodegredation.

## **METHANOL**

Persistence and degradability

SIGNIFICANT COMPARTMENTS LIKELY TO BE:~ WATER RAPID. AIR RAPID

PHOTO OXIDATION

# TETRAHYDROFURAN

Persistence and degradability

The product is expected to be biodegradable.

### PROPAN-1-OL

Persistence and degradability

SIGNIFICANT COMPARTMENTS LIKELY TO BE:~ WATER RAPID. AIR RAPID

PHOTO OXIDATION

### METHYL ACETATE

Persistence and degradability

The product is expected to be slowly biodegradable.

## **GUN WASH**

### **XYLENE**

Persistence and degradability

SIGNIFICANT COMPARTMENTS LIKELY TO BE:~ AIR RAPID PHOTO

OXIDATION SOIL MODERATE

**BUTANONE** 

Persistence and degradability

MODERATE

**ETHYLBENZENE** 

Persistence and degradability

MODERATE

**CYCLOHEXANE** 

Persistence and degradability

SIGNIFICANT COMPARTMENTS LIKELY TO BE:~ AIR RAPID PHOTO

**OXIDATION** 

PROPYL ACETATE

Persistence and degradability

RAPID.

ISOBUTYL METHYL KETONE (MIBK)

Persistence and degradability

The product is slowly degradable.

PROPAN-2-OL

Persistence and degradability

SIGNIFICANT COMPARTMENTS LIKELY TO BE:~ WATER RAPID. AIR RAPID

PHOTO OXIDATION

**HEXANE-norm** 

Persistence and degradability

The product is not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient Data lacking.

Ecological information on ingredients.

**TOLUENE** 

Bioaccumulative potential LOW

Partition coefficient : <3

**BUTYL ACETATE -norm** 

Bioaccumulative potential The product is not bioaccumulating.

## **GUN WASH**

**ACETONE** 

Bioaccumulative potential LOW ON THE BASIS OF BCF

Partition coefficient : -0.24

**METHANOL** 

Bioaccumulative potential LOW ON THE BASIS OF BCF

**TETRAHYDROFURAN** 

Bioaccumulative potential LOW ON THE BASIS OF LOG KOW

PROPAN-1-OL

Bioaccumulative potential LOW ON THE BASIS OF LOG KOW

**METHYL ACETATE** 

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of

this product.

**XYLENE** 

Bioaccumulative potential MEDIUM ON THE BASIS OF VARIABLE BCF

**BUTANONE** 

Bioaccumulative potential MODERATE

**HEPTANE** 

Bioaccumulative potential LOW

**ETHYLBENZENE** 

Bioaccumulative potential LOW

**CYCLOHEXANE** 

Bioaccumulative potential MODERATE ON THE BASIS OF LOG KOW

**PROPYL ACETATE** 

Bioaccumulative potential LOW

ISOBUTYL METHYL KETONE (MIBK)

Bioaccumulative potential LOW

Partition coefficient : 1.38

PROPAN-2-OL

Bioaccumulative potential LOW ON THE BASIS OF LOG KOW

## **GUN WASH**

**HEXANE-norm** 

Bioaccumulative potential The product is not bioaccumulating.

**BUTANOL-norm** 

Partition coefficient : P:7.6; logP: 0.88

**ETHANOL** 

Bioaccumulative potential LOW ON THE BASIS OF LOG KOW

12.4. Mobility in soil

Mobility Readily absorbed into soil

Ecological information on ingredients.

**TOLUENE** 

Mobility The product contains volatile organic compounds (VOCs) which will evaporate

easily from all surfaces.

**BUTANONE** 

**Mobility** The product is miscible with water and may spread in water systems.

**ETHYLBENZENE** 

**Mobility** The product is insoluble in water and will spread on the water surface.

**CYCLOHEXANE** 

Mobility The product contains volatile organic compounds (VOCs) which will evaporate

easily from all surfaces.

**PROPYL ACETATE** 

**Mobility** Highly mobile due to infinite water solubility.

**HEXANE-norm** 

Mobility The product contains volatile organic compounds (VOCs) which will evaporate

easily from all surfaces.

**ETHANOL** 

**Mobility** Highly mobile due to infinite water solubility.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

12.6. Other adverse effects

Other adverse effects Negligible ecotoxicity

SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Avoid release to the environment.

**Disposal methods**Transfer to a suitable container and arrange for collection by specialised disposal company.

NB the user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

Waste class 08 01 11

## SECTION 14: Transport information

### 14.1. UN number

UN No. (ADR/RID) 1263 UN No. (IMDG) 1263 UN No. (ICAO) 1263 UN No. (ADN) 1263

## 14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

PAINT RELATED MATERIAL

Proper shipping name (IMDG) PAINT RELATED MATERIAL

Proper shipping name (ICAO) PAINT RELATED MATERIAL

Proper shipping name (ADN) PAINT RELATED MATERIAL

## 14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

#### Transport labels



### 14.4. Packing group

ADR/RID packing group II
IMDG packing group II
ADN packing group II
ICAO packing group II

### 14.5. Environmental hazards

### Environmentally hazardous substance/marine pollutant



### 14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 2

Emergency Action Code •3YE

Hazard Identification Number 33

(ADR/RID)

Tunnel restriction code (D/E)

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

**Transport in bulk according to** Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Not applicable

### 15.2. Chemical safety assessment

A REACH chemical safety assessment has been carried out on the REACH registered products showing in section 3 of SDS

### SECTION 16: Other information

Abbreviations and acronyms ATE: Acute Toxicity Estimate.

used in the safety data sheet DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

CLP: Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008)]

EUH statement: CLP-specific Hazard statement

General information This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

**Issued by** Nicola Dobson, R+D Supervisor

Revision date 22/06/2017

Revision 7

Supersedes date 14/06/2017

SDS number 20846

Hazard statements in full H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H361f Suspected of damaging fertility.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Signature

N Dobson