



# SAFETY DATA SHEET

T7300 Primer Surfacer

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : T7300 Primer Surfacer  
**Product type** : Liquid.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Uses in Coatings - Priming materials and coatings

### 1.3 Details of the supplier of the safety data sheet

International Applications Ltd  
18 Wildmere Road  
Wildmere Industrial Estate  
Banbury  
Oxfordshire  
OX16 3JU  
Tel.: +44 (0) 1295 274004

**e-mail address of person responsible for this SDS** : sales@international-applications.com

### 1.4 Emergency telephone number

**Telephone number** : Call: +44 (0) 1295 274004

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226  
Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

#### Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : R10  
R67  
N; R51/53

**Physical/chemical hazards** : Flammable.

**Human health hazards** : Vapours may cause drowsiness and dizziness.

## SECTION 2: Hazards identification


**Environmental hazards** : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Warning

**Hazard statements** : Flammable liquid and vapour.  
Toxic to aquatic life with long lasting effects.

### Precautionary statements

**Prevention** : Wear protective gloves. Wear eye/face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Avoid release to the environment.

**Response** : IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

**Storage** : Keep cool.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Supplemental label elements** : Contains methyl methacrylate. May produce an allergic reaction.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### Special packaging requirements

**Containers to be fitted with child-resistant fastenings** : Not applicable.

**Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	w%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	

**SECTION 3: Composition/information on ingredients**

n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≥10 - <20	R10 R66, R67	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	<10	R10 Xn; R20/21 Xi; R38	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Flam. Liq. 3, H226	[1] [2]
2-methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	≤5	R10	Flam. Liq. 3, H226	[2]
trizinc bis (orthophosphate)	REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	≤5	N; R50/53	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≤3	F; R11 Xn; R20, R48/20, R65	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	[1] [2]
zinc oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≤1	N; R50/53	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
zinc 5-nitroisophthalate	EC: 262-309-9 CAS: 60580-61-2	≤1	R52/53	Aquatic Chronic 1, H410 (M=1)	[1]
toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3	≤0.3	F; R11 Repr. Cat. 3; R63 Xn; R48/20, R65 Xi; R38 R67	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d (Unborn child) STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304	[1] [2]
methyl methacrylate	REACH #: 01-2119452498-28 EC: 201-297-1 CAS: 80-62-6 Index: 607-035-00-6	≤0.3	F; R11 Xi; R37/38 R43	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335	[1] [2]
			<b>See Section 16 for the full text of the R-phrases declared above.</b>	<b>See Section 16 for the full text of the H statements declared above.</b>	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

## SECTION 3: Composition/information on ingredients

- [1] Substance classified with a health or environmental hazard  
 [2] Substance with a workplace exposure limit  
 [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII  
 [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII  
 [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains methyl methacrylate. May produce an allergic reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

**Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

: Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from

## SECTION 7: Handling and storage

sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

### Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	<b>EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b> STEL: 442 mg/m <sup>3</sup> , 0 times per shift, 15 minutes. STEL: 100 ppm, 0 times per shift, 15 minutes. TWA: 221 mg/m <sup>3</sup> , 0 times per shift, 8 hours. TWA: 50 ppm, 0 times per shift, 8 hours.
2-methoxy-1-methylethyl acetate	<b>EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b> TWA: 50 ppm 8 hours. TWA: 275 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 550 mg/m <sup>3</sup> 15 minutes.
ethylbenzene	<b>EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b> STEL: 884 mg/m <sup>3</sup> 15 minutes. STEL: 200 ppm 15 minutes. TWA: 442 mg/m <sup>3</sup> 8 hours. TWA: 100 ppm 8 hours.
toluene	<b>EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list</b>

**SECTION 8: Exposure controls/personal protection**

methyl methacrylate	<p><b>of indicative occupational exposure limit values</b>                  STEL: 384 mg/m<sup>3</sup> 15 minutes.                  STEL: 100 ppm 15 minutes.                  TWA: 192 mg/m<sup>3</sup> 8 hours.                  TWA: 50 ppm 8 hours.</p> <p><b>EU OEL (Europe, 12/2009). Notes: list of indicative occupational exposure limit values</b>                  TWA: 50 ppm 8 hours.                  STEL: 100 ppm 15 minutes.</p>
---------------------	---

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

Product/ingredient name	Type	Exposure	Value	Population	Effects
n-butyl acetate	DNEL	Short term Inhalation	960 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	960 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	480 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	480 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	859.7 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Short term Inhalation	859.7 mg/m <sup>3</sup>	Consumers	Local
	DNEL	Long term Inhalation	102.34 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Long term Inhalation	102.34 mg/m <sup>3</sup>	Consumers	Local
xylene	DNEL	Short term Inhalation	289 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	289 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	180 mg/kg	Workers	Systemic
	DNEL	Short term Inhalation	174 mg/m <sup>3</sup>	Consumers	Local
	DNEL	Short term Inhalation	174 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Long term Inhalation	14.8 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Long term Dermal	108 mg/kg	Consumers	Systemic
2-methoxy-1-methylethyl acetate	DNEL	Long term Oral	1.6 mg/kg	Consumers	Systemic
	DNEL	Long term Dermal	153.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	275 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Long term Dermal	54.8 mg/	Consumers	Systemic

**SECTION 8: Exposure controls/personal protection**

trizinc bis(orthophosphate)	DNEL	Long term Inhalation	kg bw/day 33 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Oral	1.67 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	5 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	83 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	83 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Inhalation	2.5 mg/m <sup>3</sup>	Consumers	Systemic
ethylbenzene	DNEL	Long term Oral	0.83 mg/ kg bw/day	Consumers	Systemic
	DNEL	Long term Inhalation	77 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	15 mg/m <sup>3</sup>	Consumers	Systemic
zinc oxide	DNEL	Long term Oral	1.6 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Inhalation	5 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	2.5 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Long term Oral	0.83 mg/ kg bw/day	Consumers	Systemic
toluene	DNEL	Long term Dermal	87 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	87 mg/kg bw/day	Consumers	Systemic
	DNEL	Short term Inhalation	384 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	384 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	192 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	192 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	384 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	226 mg/m <sup>3</sup>	Consumers	Local
	DNEL	Short term Inhalation	226 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Long term Inhalation	56.5 mg/m <sup>3</sup>	Consumers	Systemic
methyl methacrylate	DNEL	Long term Dermal	226 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Oral	8.13 mg/ kg bw/day	Consumers	Systemic
	DNEL	Long term Inhalation	208 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	208 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Dermal	13.67 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	1.5 mg/cm <sup>2</sup>	Workers	Local
	DNEL	Short term Dermal	1.5 mg/cm <sup>2</sup>	Workers	Local
	DNEL	Long term	74.3 mg/m <sup>3</sup>	Consumers	Systemic



**SECTION 8: Exposure controls/personal protection**

	DNEL	Inhalation Long term Inhalation	104 mg/m <sup>3</sup>	Consumers	Local
	DNEL	Long term Dermal	8.2 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Dermal	1.5 mg/cm <sup>2</sup>	Consumers	Local
	DNEL	Short term Dermal	1.5 mg/cm <sup>2</sup>	Consumers	Local

**PNECs**

Product/ingredient name	Compartment Detail	Value	Method Detail
n-butyl acetate	Fresh water	0.18 mg/l	-
	Marine	0.018 mg/l	-
	Fresh water sediment	0.981 mg/kg	-
	Marine water sediment	0.0981 mg/kg	-
	Soil	0.0903 mg/kg	-
	Sewage Treatment Plant	35.6 mg/l	-
	xylene	Fresh water	0.327 mg/l
Marine water		0.327 mg/l	-
Fresh water sediment		12.46 mg/kg	-
Marine water sediment		12.46 mg/kg	-
Soil		2.31 mg/kg	-
Sewage Treatment Plant		6.58 mg/l	-
2-methoxy-1-methylethyl acetate		Fresh water	0.635 mg/l
	Marine	0.0635 mg/l	-
	Sewage Treatment Plant	100 mg/l	-
	Fresh water sediment	3.29 mg/kg	-
	Marine water sediment	0.329 mg/kg	-
	Soil	0.29 mg/kg	-
	trizinc bis(orthophosphate)	Fresh water	20.6 µg/l
Marine water		6.1 µg/l	-
Fresh water sediment		117.8 mg/kg dwt	-
Marine water sediment		56.5 mg/kg dwt	-
Soil		35.6 mg/kg dwt	-
Sewage Treatment Plant		100 µg/l	-
ethylbenzene		Fresh water	0.1 mg/l
	Marine water	0.01 mg/l	-
	Fresh water sediment	13.7 mg/kg	-
	Marine water sediment	1.37 mg/kg	-
	Soil	2.68 mg/kg	-
	Sewage Treatment Plant	9.6 mg/l	-
	zinc oxide	Fresh water	20.6 µg/l
Marine water		6.1 µg/l	-
Fresh water sediment		117 mg/kg dwt	-
Sewage Treatment Plant		52 µg/l	-
Marine water sediment		56.5 mg/kg dwt	-
Soil		35.6 mg/kg dwt	-
toluene		Fresh water	0.68 mg/l
	Marine water	0.68 mg/l	-
	Fresh water sediment	16.39 mg/l	-
	Marine water sediment	16.39 mg/l	-
	Soil	2.89 mg/kg	-
	Sewage Treatment Plant	13.61 mg/l	-
	methyl methacrylate	Fresh water	0.94 mg/l
Marine water		0.94 mg/l	Assessment Factors

## SECTION 8: Exposure controls/personal protection

	Sewage Treatment Plant	10 mg/l	Assessment Factors
	Fresh water sediment	5.74 mg/kg dwt	Equilibrium Partitioning
	Soil	1.47 mg/kg dwt	Equilibrium Partitioning

### 8.2 Exposure controls

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: chemical splash goggles and/or face shield.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Recommended EN 374 polyvinyl alcohol (PVA) butyl rubber  $\geq 0.7$  mm  
< 1 hour (breakthrough time): Conditionally suitable materials for protective gloves; EN 374: Nitrile rubber - NBR ( $\geq 0.35$  mm). Only suitable as splash protection. Only suitable for brief exposure. In the event of contamination, change protective gloves immediately.

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. Recommended: Cotton or cotton/synthetic overalls or coveralls are normally suitable.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## SECTION 8: Exposure controls/personal protection

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: EN 405:2001 + A1:2009 organic vapour (Type A) and particulate filter FFA2P3 R D

**Environmental exposure controls** : Do not allow to enter drains or watercourses.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid.  
**Colour** : Grey.  
**Odour** : Not available.  
**Odour threshold** : Not available.  
**pH** : Not available.  
**Melting point/freezing point** : Not available.  
**Initial boiling point and boiling range** : >100°C  
**Flash point** : Closed cup: 26°C  
**Evaporation rate** : Not available.  
**Upper/lower flammability or explosive limits** : Not available.  
**Vapour pressure** : Not available.  
**Vapour density** : Not available.  
**Relative density** : 1.467  
**Solubility(ies)** : Insoluble in the following materials: cold water and hot water.  
**Partition coefficient: n-octanol/ water** : Not available.  
**Auto-ignition temperature** : Not available.  
**Decomposition temperature** : Not available.  
**Viscosity** : Not available.  
**Explosive properties** : Not available.  
**Oxidising properties** : Not available.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

**SECTION 10: Stability and reactivity**

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**SECTION 11: Toxicological information****11.1 Information on toxicological effects**

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains methyl methacrylate. May produce an allergic reaction.

**Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
n-butyl acetate	LC50 Inhalation Vapour	Rat	>21.1 mg/l	4 hours
	LD50 Dermal	Rabbit	>14112 mg/kg	-
xylene	LD50 Oral	Rat	10760 mg/kg	-
	LC50 Inhalation Vapour	Rat	27.6 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
2-methoxy-1-methylethyl acetate	LD50 Oral	Rat	>2000 mg/kg	-
	LD50 Dermal	Rat	>5000 mg/kg	-
trizinc bis(orthophosphate)	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5.7 mg/l	4 hours
ethylbenzene	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapour	Rat	>9.6 mg/l	4 hours
	LD50 Dermal	Rabbit	>15000 mg/kg	-
zinc oxide	LD50 Oral	Rat	>3500 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	>5.7 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
toluene	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapour	Rat	28.1 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
methyl methacrylate	LD50 Oral	Rat	5580 mg/kg	-
	LC50 Inhalation Vapour	Rat - Male, Female	29.8 mg/l	4 hours
	LD50 Dermal	Rabbit	5000 mg/kg	-
	LD50 Oral	Rat	7872 mg/kg	-

**Conclusion/Summary** : Not available.

**Acute toxicity estimates**

Route	ATE value
Dermal	13173.1 mg/kg
Inhalation (vapours)	108.5 mg/l

**Irritation/Corrosion**

## SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	100 Percent	-
	Eyes - Mild irritant	Rabbit	-	87 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
ethylbenzene	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-
zinc oxide	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 milligrams	-
	Eyes - Mild irritant	Rabbit	-	870 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Pig	-	24 hours 250 microliters	-
	Skin - Mild irritant	Rabbit	-	435 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Skin - Moderate irritant	Rabbit	-	500 milligrams	-

**Conclusion/Summary** : Not available.

**Sensitisation**

**Conclusion/Summary** : Not available.

**Mutagenicity**

**Conclusion/Summary** : Not available.

**Carcinogenicity**

**Conclusion/Summary** : Not available.

**Reproductive toxicity**

**Conclusion/Summary** : Not available.

**Teratogenicity**

**Conclusion/Summary** : Not available.

**Specific target organ toxicity (single exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
n-butyl acetate	Category 3	Not applicable.	Narcotic effects
xylene	Category 3	Not applicable.	Respiratory tract irritation
toluene	Category 3	Not applicable.	Narcotic effects
methyl methacrylate	Category 3	Not applicable.	Respiratory tract irritation

**Specific target organ toxicity (repeated exposure)**

## SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
xylene	Category 2	Not determined	Not determined
ethylbenzene	Category 2	Not determined	hearing organs
toluene	Category 2	Not determined	Not determined

### Aspiration hazard

Product/ingredient name	Result
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1
toluene	ASPIRATION HAZARD - Category 1

**Other information** : Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
n-butyl acetate	Acute EC50 647.7 mg/l	Algae - Desmodesmus subspicatus	72 hours
	Acute EC50 44 mg/l	Daphnia	48 hours
	Acute LC50 32 mg/l	Crustaceans - Artemia salina	48 hours
	Acute LC50 18 mg/l	Fish - Pimephales promelas	96 hours
	Acute NOEC 200 mg/l	Algae	72 hours
	Chronic NOEC 23 mg/l	Daphnia - Daphnia magna	21 days
xylene	Acute EC50 1 to 10 mg/l	Algae	72 hours
	Acute EC50 1 to 10 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 1 to 10 mg/l	Fish	96 hours
2-methoxy-1-methylethyl acetate	Acute EC50 >1000 mg/l	Algae - Pseudokirchnerella subcapitata	96 hours
	Acute EC50 408 mg/l	Daphnia - Daphnia magna	48 hours
trizinc bis(orthophosphate)	Acute LC50 134 mg/l	Fish - Oncorhynchus mykiss	96 hours
	Acute EC50 63.1 mg/l	Daphnia - Daphnia magna	48 hours
ethylbenzene	Acute LC50 6.3 mg/l	Fish - Oncorhynchus mykiss	96 hours
	Acute EC50 >1.8 mg/l	Daphnia - Daphnia magna	48 hours
zinc oxide	Acute LC50 >10 mg/l	Fish - Pimephales promelas	96 hours
	Acute EC50 0.17 mg/l	Algae - Selenastrum capricornutum	72 hours
toluene	Acute LC50 320 ppm	Fish - Lepomis macrochirus	96 hours
	Chronic NOEC 0.017 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 12.5 mg/l	Algae	72 hours
methyl methacrylate	Acute EC50 3.8 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 5.5 mg/l	Fish - Oncorhynchus kisutch	96 hours
	Acute EC50 >110 mg/l Fresh water	Algae - Pseudokirchnerella subcapitata	72 hours
	Acute EC50 69 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 130 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute NOEC 49 mg/l Fresh water	Algae - Pseudokirchnerella subcapitata	72 hours
	Chronic NOEC 37 mg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 9.4 mg/l Fresh water	Fish - Danio rerio	35 days

**Conclusion/Summary** : Not available.

**SECTION 12: Ecological information****12.2 Persistence and degradability**

Product/ingredient name	Test	Result	Dose	Inoculum
n-butyl acetate	OECD 301D Ready Biodegradability - Closed Bottle Test	>80 % - 5 days	-	-
2-methoxy-1-methylethyl acetate	OECD 302B Inherent Biodegradability: Zahn-Wellens/ EMPA Test	100 % - 28 days	-	-
	OECD 301F Ready Biodegradability - Manometric Respirometry Test	83 % - 28 days	-	-

**Conclusion/Summary** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
n-butyl acetate	-	-	Readily
2-methoxy-1-methylethyl acetate	-	-	Readily
toluene	-	-	Readily

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
n-butyl acetate	2.3	-	low
xylene	3.12	8.1 to 25.9	low
2-methoxy-1-methylethyl acetate	1.2	-	low
trizinc bis(orthophosphate)	-	60960	high
ethylbenzene	3.6	-	low
zinc oxide	-	60960	high
toluene	2.73	90	low
methyl methacrylate	1.38	-	low

**12.4 Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

**12.5 Results of PBT and vPvB assessment**

**PBT** : Not applicable.

**vPvB** : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### Packaging







**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

<b>Type of packaging</b> CEPE Paint Guidelines	15 01 10*	<b>European waste catalogue (EWC)</b> packaging containing residues of or contaminated by hazardous substances
---	-----------	---

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number</b>	UN1263	UN1263	UN1263	UN1263
<b>14.2 UN proper shipping name</b>	PAINT	PAINTPAINT	PAINT	Paint
<b>14.3 Transport hazard class(es)</b>	3  	3  	3 	3 
<b>14.4 Packing group</b>	III	III	III	III
<b>14.5 Environmental hazards</b>	Yes.	Yes.	No.	No.



## SECTION 14: Transport information

<p><b>Additional information</b></p>	<p>The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.</p> <p><b>Hazard identification number</b> 30</p> <p><b>Limited quantity</b> 5 L</p> <p><b>Special provisions</b> 163, 640E, 650</p> <p><b>Tunnel code</b> (D/E)</p>	<p>The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.</p> <p><b>Special provisions</b> 163, 640E, 650</p>	<p><b>Emergency schedules (EmS)</b> F-E, _S-E_</p> <p><b>Special provisions</b> 163, 223, 955</p>	<p>The environmentally hazardous substance mark may appear if required by other transportation regulations.</p> <p><b>Passenger and Cargo Aircraft</b> Quantity limitation: 60 L Packaging instructions: 355</p> <p><b>Cargo Aircraft Only</b> Quantity limitation: 220 L Packaging instructions: 366</p> <p><b>Limited Quantities - Passenger Aircraft</b> Quantity limitation: 10 L Packaging instructions: Y344</p> <p><b>Special provisions</b> A3, A72</p>
--------------------------------------	--	---	---	---

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** : Not applicable.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other EU regulations

**VOC** : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

**Europe inventory** : Not determined.

## SECTION 15: Regulatory information

Product/ingredient name	Carcinogenic effects	Mutagenic effects	Developmental effects	Fertility effects
toluene	-	-	Repr. 2, H361d (Unborn child)	-

### Ozone depleting substances (1005/2009/EU)

Not listed.

### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

### Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

**Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol (Annexes A, B, C, E)

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Inform Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### International lists

#### National inventory

- Australia** : At least one component is not listed.
- Canada** : At least one component is not listed.
- China** : Not determined.
- Japan** : **Japan inventory (ENCS)**: At least one component is not listed.  
**Japan inventory (ISHL)**: Not determined.
- Malaysia** : Not determined.
- New Zealand** : Not determined.
- Philippines** : Not determined.
- Republic of Korea** : At least one component is not listed.
- Taiwan** : Not determined.
- Turkey** : Not determined.
- United States** : Not determined.

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information****CEPE code** : 1

✔ Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- vPvB = Very Persistent and Very Bioaccumulative

**Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Classification	Justification
Flam. Liq. 3, H226 Aquatic Chronic 2, H411	On basis of test data Calculation method

**Full text of abbreviated H statements**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d (Unborn child)	Suspected of damaging the unborn child.
H373 (hearing organs)	May cause damage to organs through prolonged or repeated exposure. (hearing organs)
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Full text of classifications [CLP/GHS]**

Acute Tox. 4, H312	ACUTE TOXICITY (dermal) - Category 4
Acute Tox. 4, H332	ACUTE TOXICITY (inhalation) - Category 4
Aquatic Acute 1, H400	ACUTE AQUATIC HAZARD - Category 1
Aquatic Chronic 1, H410	LONG-TERM AQUATIC HAZARD - Category 1
Aquatic Chronic 2, H411	LONG-TERM AQUATIC HAZARD - Category 2
Aquatic Chronic 3, H412	LONG-TERM AQUATIC HAZARD - Category 3
Asp. Tox. 1, H304	ASPIRATION HAZARD - Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 2, H225	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3, H226	FLAMMABLE LIQUIDS - Category 3
Repr. 2, H361d (Unborn child)	TOXIC TO REPRODUCTION (Unborn child) - Category 2
Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1, H317	SKIN SENSITIZATION - Category 1
STOT RE 2, H373 (hearing organs)	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (hearing organs) - Category 2
STOT RE 2, H373	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
STOT SE 3, H335	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
STOT SE 3, H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)

**SECTION 16: Other information**

(Narcotic effects) - Category 3

**Full text of abbreviated R phrases**

R11- Highly flammable.

R10- Flammable.

R63- Possible risk of harm to the unborn child.

R20- Harmful by inhalation.

R20/21- Harmful by inhalation and in contact with skin.

R48/20- Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R65- Harmful: may cause lung damage if swallowed.

R38- Irritating to skin.

R37/38- Irritating to respiratory system and skin.

R43- May cause sensitisation by skin contact.

R66- Repeated exposure may cause skin dryness or cracking.

R67- Vapours may cause drowsiness and dizziness.

R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Full text of classifications [DSD/DPD]**

F - Highly flammable

Repr. Cat. 3 - Toxic to reproduction category 3

Xn - Harmful

Xi - Irritant

N - Dangerous for the environment

**Date of printing** : 22/11/2016**Date of issue/ Date of revision** : 22/11/2016**Date of previous issue** : No previous validation**Version** : 1**Notice to reader**

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.