



Etalon Fine Putty

gb 1/1211

Product Information

page 1 / 1

Etalon Fine Putty is a bright-white especially easily sandable 2-component finishing putty based on polyester resins with adhesion on iron, steel, aluminium, zinc and glass fibre reinforced compounds. Because of its fine structure and excellent covering power Etalon Fine Putty is suited as top and finishing putty for an application in very thin coats or as top layer above polyester filling putties in order to close possible pin holes, small irregularities, small paint damages or scratches on the car body. An application on vertical substrates is possible without problems.

Colour shade	bright white			
Mixing ratio	100 : 2			
Hardener	hardener white or red			
Thinners				
Spraying viscosity 20° C				
Application	Spraying pressure	spraying nozzle	spraying operations	
Air / Flowjar - Spray gun				
Airless / Airmix				
Pot life	4 - 5 min.			
Coat thickness / dry film				
Curing time / Flash off time				
Dry	recoat time	dust dry	set to touch	full hardness
Object Temp. 20° C Object Temp. 60° C infra-red curing	Sandable after 15 - 20 min. Sandable after approx. 10 min.			
VOC content	EU limiting value for the product (cat. B/b): 250 g/l (2007) This product contains max. 4 g/l VOC [0.033 lbs/gal]			

Remarks:

The substrate must be clean, dry and free of grease. Sand the surface to provide an improved key. The existing coating which is not in good condition and firmly adhering should be sufficiently sanded to remove all traces of old paint or primer. Do not apply on thermoplastic or acid-containing products. Mix putty and hardener properly.