

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: *ETACLEAR SR ACRYLIC CLEAR COAT 2:1*

1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses: professional use.
Application of the substance / the mixture Clear coating material, Varnish

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Alexport Company

Pontou 26, P.C. 546 28, Thessaloniki, Greece

Tel: +30 2310 501814, Fax: +30 2310 524 771

www.etalon.gr

Further information obtainable from: info@alexport.gr

1.4 Emergency telephone number: 122 or call your doctor/local poison center

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02



GHS07

Signal word Warning

Hazard-determining components of labelling:

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

hydrocarbons, C9, aromatics

n-butyl acetate

xylene

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2015

V- 1

Revision: 03.06.2015

Trade name: ETACLEAR SR ACRYLIC CLEAR COAT 2:1

(Contd. of page 1)

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	10-25%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	5-15%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	5-15%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	1-7.5%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	1-5%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-butoxyethyl acetate ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332	1-5%
EC number: 915-687-0 Reg.nr.: 01-2119491304-40	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Sens. 1A, H317	0.1-<0.5%
CAS: 127519-17-9 ELINCS: 407-000-3 Reg.nr.: 01-0000015648-61	reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates ⚠ Aquatic Chronic 2, H411	0.1-<0.5%

Additional information: For the wording of the listed risk phrases refer to section 16.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2015

V- 1

Revision: 03.06.2015

Trade name: ETACLEAR SR ACRYLIC CLEAR COAT 2:1

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Take affected persons out of danger area and lay down.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Avoid contact with the eyes and skin.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2015

V- 1

Revision: 03.06.2015

Trade name: ETACLEAR SR ACRYLIC CLEAR COAT 2:1

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not allow to enter sewers/ surface or ground water.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:	
123-86-4 n-butyl acetate	
WEL (Great Britain)	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
1330-20-7 xylene	
WEL (Great Britain)	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
1330-20-7 xylene	
WEL (Great Britain)	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2015

V- 1

Revision: 03.06.2015

Trade name: ETACLEAR SR ACRYLIC CLEAR COAT 2:1

(Contd. of page 4)

108-65-6 2-methoxy-1-methylethyl acetate	
WEL (Great Britain)	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
IOELV (EU)	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin
100-41-4 ethylbenzene	
WEL (Great Britain)	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
IOELV (EU)	Short-term value: 884 mg/m ³ , 200 ppm Long-term value: 442 mg/m ³ , 100 ppm Skin
112-07-2 2-butoxyethyl acetate	
WEL (Great Britain)	Short-term value: 332 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Sk
IOELV (EU)	Short-term value: 333 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Skin
DNELs	
123-86-4 n-butyl acetate	
Dermal	DNEL 7 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL 960 mg/m ³ (acute - systemic effects, workers) 960 mg/m ³ (acute - local effects, workers) 480 mg/m ³ (long-term - systemic effects, workers) 480 mg/m ³ (long-term - local effects, workers)
hydrocarbons, C9, aromatics	
Dermal	DNEL 25 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL 150 mg/m ³ (long-term - systemic effects, workers)
1330-20-7 xylene	
Dermal	DNEL 180 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL 289 mg/m ³ (acute - systemic effects, workers) 289 mg/m ³ (acute - local effects, workers) 77 mg/m ³ (long-term - systemic effects, workers) 77 mg/m ³ (long-term - local effects, workers)
108-65-6 2-methoxy-1-methylethyl acetate	
Dermal	DNEL 153.5 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL 275 mg/m ³ (long-term - systemic effects, workers)
100-41-4 ethylbenzene	
Dermal	DNEL 180 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL 293 mg/m ³ (acute - local effects, workers) 77 mg/m ³ (long-term - systemic effects, workers)
112-07-2 2-butoxyethyl acetate	
Dermal	DNEL 102 mg/kg bw/day (acute - systemic effects, workers) 102 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL 775 mg/m ³ (acute - systemic effects, workers)

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2015

V- 1

Revision: 03.06.2015

Trade name: ETACLEAR SR ACRYLIC CLEAR COAT 2:1

(Contd. of page 5)

		333 mg/m ³ (acute - local effects, workers) 133 mg/m ³ (long-term - local effects, workers)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		
Dermal	DNEL	2.5 mg/kg bw/day (acute - systemic effects, workers) 2.5 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	2.35 mg/m ³ (acute - systemic effects, workers) 2.35 mg/m ³ (long-term - systemic effects, workers)
127519-17-9 reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates		
Dermal	DNEL	0.83 mg/kg bw/day (long-term - systemic effects, workers)
Inhalative	DNEL	7 mg/m ³ (long-term - systemic effects, workers)
PNECs		
123-86-4 n-butyl acetate		
PNEC		0.18 mg/l (freshwater environment) 0.018 mg/l (marine environment) 0.36 mg/l (intermittent releases) 0.981 mg/kg (freshwater sediment environment) 35.6 mg/l (sewage treatment plants)
1330-20-7 xylene		
PNEC		0.327 mg/l (freshwater environment) 12.46 mg/kg (freshwater sediment environment) 2.31 mg/kg (soil) 6.58 mg/l (sewage treatment plants)
108-65-6 2-methoxy-1-methylethyl acetate		
PNEC		0.635 mg/l (freshwater environment) 0.0635 mg/l (marine environment) 6.35 mg/l (intermittent releases) 3.29 mg/kg (freshwater sediment environment) 0.329 mg/kg (marine sediment environment) 100 mg/l (sewage treatment plants)
100-41-4 ethylbenzene		
PNEC		0.1 mg/l (freshwater environment) 0.01 mg/l (marine environment) 0.1 mg/l (intermittent releases) 13.7 mg/kg (freshwater sediment environment) 1.37 mg/kg (marine sediment environment) 2.68 mg/kg (soil) 9.6 mg/l (sewage treatment plants)
112-07-2 2-butoxyethyl acetate		
PNEC		0.304 mg/l (freshwater environment) 0.0304 mg/l (marine environment) 0.56 mg/l (intermittent releases) 2.03 mg/kg (freshwater sediment environment) 0.203 mg/kg (marine sediment environment) 0.68 mg/kg (soil)

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2015

V- 1

Revision: 03.06.2015

Trade name: ETACLEAR SR ACRYLIC CLEAR COAT 2:1

(Contd. of page 6)

	90 mg/l (sewage treatment plants)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
PNEC	0.0022 mg/l (freshwater environment) 0.00022 mg/l (marine environment) 0.009 mg/l (intermittent releases) 1.05 mg/kg (freshwater sediment environment) 0.11 mg/kg (marine sediment environment) 0.21 mg/kg (soil)
127519-17-9 reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates	
PNEC	0.0425 mg/l (freshwater environment) 0.00425 mg/l (marine environment) 0.032 mg/l (intermittent releases) 3520 mg/kg (freshwater sediment environment) 352 mg/kg (marine sediment environment) 701 mg/kg (soil) 10 mg/l (sewage treatment plants)
Ingredients with biological limit values:	
1330-20-7 xylene	
BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
1330-20-7 xylene	
BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Keep ignition sources away - Do not smoke.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

Use suitable respiratory protective device in case of insufficient ventilation.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2015

V- 1

Revision: 03.06.2015

Trade name: ETACLEAR SR ACRYLIC CLEAR COAT 2:1

(Contd. of page 7)

Protection of hands:

Protective gloves

Check the permeability prior to each renewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (EN 374).

Material of gloves

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

PVA gloves

Recommended thickness of the material: $\geq 0,7$ mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Value for the permeation: Level 6 ≥ 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Appearance:**

Form:	Fluid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value: Not applicable.

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124 °C Undetermined.

Flash point: 40 °C

Flammability (solid, gaseous): Not applicable.

Decomposition temperature: Not determined.

Auto-ignition temperature: Not determined.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower: 0.7 Vol %

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2015

V- 1

Revision: 03.06.2015

Trade name: ETACLEAR SR ACRYLIC CLEAR COAT 2:1

(Contd. of page 8)

Upper:	15.0 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	0.96 g/cm ³
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic at 20 °C:	107 mPas
Kinematic:	Not determined.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No decomposition if used according to specifications.

10.2 Chemical stability No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Reacts with alkali, amines and strong acids.

Reacts with oxidising agents.

Fumes can combine with air to form an explosive mixture.

10.4 Conditions to avoid Protect from heat and direct sunlight.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD/LC50 values relevant for classification:		
123-86-4 n-butyl acetate		
Oral	LD50	10760 mg/kg (rat)
Dermal	LD50	10760 mg/kg (rat)
		>14000 mg/kg (rabbit)
Inhalative	LC50/4 h	23.4 mg/l (rat)
hydrocarbons, C9, aromatics		
Oral	LD50	3592 mg/kg (rat)
Dermal	LD50	>3160 mg/kg (-)
Inhalative	LC50/4 h	> 6193 mg/l (rat)
1330-20-7 xylene		
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)
1330-20-7 xylene		
Oral	ATE	>2000 mg/kg (-)
Dermal	ATE	1466.67 mg/kg (-)
Inhalative	ATE	12.09 mg/l (-) (vapour)

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2015

V- 1

Revision: 03.06.2015

Trade name: ETACLEAR SR ACRYLIC CLEAR COAT 2:1

(Contd. of page 9)

108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/6 h	4345 mg/l (rat)
100-41-4 ethylbenzene		
Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)
112-07-2 2-butoxyethyl acetate		
Oral	LD50	1880 mg/kg (rat)
Dermal	LD50	1500 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		
Oral	LD50	3230 mg/kg (rat)
Dermal	LD50	>3170 mg/kg (rat)
127519-17-9 reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

Primary irritant effect:**Skin corrosion/irritation**

Causes skin irritation.

Serious eye damage/irritation Based on available data, the classification criteria are not met.**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure**

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:****123-86-4 n-butyl acetate**

EC50/48 h	44 mg/l (daphnia)
EC50/72 h	675 mg/l (algae)
LC50/96 h	18 mg/l (Pimephales promelas)
TT/16 h	115 mg/l (Pseudomonas putida)

hydrocarbons, C9, aromatics

EC50/10 min	>99 mg/l (microorganisms)
EC50/48 h	6.14 mg/l (Daphnia magna)
EL50/48 h	3.2 mg/l (Daphnia magna)
ErC50/96 h	9.2 mg/l (fish)

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2015

V- 1

Revision: 03.06.2015

Trade name: ETACLEAR SR ACRYLIC CLEAR COAT 2:1

(Contd. of page 10)

ErL50/72 h	2.9 mg/l (<i>Pseudokirchnerella subcapitata</i>)
1330-20-7 xylene	
EC50/24 h	96 mg/l (microorganisms)
EC50/48 h	>1-10 mg/l (<i>Daphnia magna</i>)
IC50/72 h	2.2 mg/l (algae)
LC50/96 h	2.6 mg/l (fish)
108-65-6 2-methoxy-1-methylethyl acetate	
EC20/30 min	>1000 mg/l (microorganisms)
EC50	>100 mg/l (<i>Pseudokirchnerella subcapitata</i>) >100 mg/l (<i>Pimephales promelas</i>) >100 mg/l (<i>Daphnia magna</i>)
EC50/48 h	>500 mg/l (<i>Daphnia magna</i>)
EC50/72 h	>1000 mg/l (<i>Pseudokirchnerella subcapitata</i>)
LC50/96 h	>100 mg/l (fish)
100-41-4 ethylbenzene	
EC20/30 min	200 mg/l (microorganisms)
EC50/24 h	13.4 mg/l (algae) 7 mg/l (fish)
EC50/48 h	2.4 mg/l (<i>Daphnia magna</i>)
112-07-2 2-butoxyethyl acetate	
EC50/24 h	>100 mg/l (<i>Daphnia magna</i>)
EC50/72 h	>100 mg/l (<i>Scenedesmus subspicatus</i>)
LC50/48 h	10-100 mg/l (<i>Leuciscus idus melanotus</i>)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
EC50/24 h	20 mg/l (<i>Daphnia magna</i>)
EC50/3 h	>100 mg/l (microorganisms)
EC50/72 h	1.68 mg/l (<i>Desmodesmus subspicatus</i>)
LC50/96 h	0.97 mg/l (fish)
127519-17-9 reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates	
EC20/30 min	>100 mg/l (microorganisms)
EC50/24 h	16.4 mg/l (invertebrates)
EC50/72 h	>2 mg/l (<i>Scenedesmus subspicatus</i>)
LC50/96 h	>9.9 mg/l (fish)
12.2 Persistence and degradability	
123-86-4 n-butyl acetate	
Biodegradation	83 % (readily biodegradable) (OECD 301 D, 28 d, aerobic)
hydrocarbons, C9, aromatics	
Biodegradation	78 % (readily biodegradable) (OECD 301 F, 28 d, aerobic)
1330-20-7 xylene	
Biodegradation	>60 % (readily biodegradable) (OECD 301 F, 28 d, aerobic)
108-65-6 2-methoxy-1-methylethyl acetate	
Biodegradation	100 % (readily biodegradable) (OECD 302 B, 8 d, aerobic)
100-41-4 ethylbenzene	
Biodegradation	100 % (readily biodegradable) (OECD 301 E, 6 d, aerobic)

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2015

V- 1

Revision: 03.06.2015

Trade name: ETACLEAR SR ACRYLIC CLEAR COAT 2:1

(Contd. of page 11)

112-07-2 2-butoxyethyl acetate	
Biodegradation	>70 % (readily biodegradable) (OECD 301C, 28d)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
Biodegradation	38 % (not readily biodegradable) (OECD 301 F, 28 d, aerobic)
127519-17-9 reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates	
Biodegradation	9 % (not readily biodegradable)
12.3 Bioaccumulative potential	
123-86-4 n-butyl acetate	
BCF	15.3 (-)
log Pow	2.3 (-)
1330-20-7 xylene	
BCF	25.9 (-)
log Pow	3.15 (-)
108-65-6 2-methoxy-1-methylethyl acetate	
log Pow	0.56 (-)
100-41-4 ethylbenzene	
BCF	1 (-)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
BCF	<9.7 (-)
127519-17-9 reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates	
BCF	<0.24 (-)
12.4 Mobility in soil	
123-86-4 n-butyl acetate	
log Koc	1.27 (-)
108-65-6 2-methoxy-1-methylethyl acetate	
Koc	1.7 (-)
100-41-4 ethylbenzene	
log Koc	2.41 (-)
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	
Koc	204400 (-)
log Koc	5.31 (-)
127519-17-9 reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates	
Koc	827300 (-)
log Koc	5.9177 (-)

Additional ecological information:**General notes:**

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2015

V- 1

Revision: 03.06.2015

Trade name: **ETACLEAR SR ACRYLIC CLEAR COAT 2:1**

(Contd. of page 12)

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11* | waste paint and varnish containing organic solvents or other dangerous substances

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****14.1 UN-Number**

ADR, IMDG, IATA

UN1263

14.2 UN proper shipping name

ADR

1263 PAINT

IMDG, IATA

PAINT

14.3 Transport hazard class(es)

ADR, IMDG, IATA



Class

3

Label

3

14.4 Packing group

ADR, IMDG, IATA

III

14.5 Environmental hazards:

Marine pollutant (IMDG):

No

14.6 Special precautions for user

Warning: Flammable liquids.

Danger code (Kemler):

30

EMS Number:

F-E, S-E

14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

Transport/Additional information:**ADR**

Limited quantities (LQ)

5L

Transport category

3

Tunnel restriction code

D/E

IMDG

Limited quantities (LQ)

5L

UN "Model Regulation":

UN1263, PAINT, 3, III

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.06.2015

V- 1

Revision: 03.06.2015

Trade name: ETACLEAR SR ACRYLIC CLEAR COAT 2:1

(Contd. of page 13)

Directive 2012/18/EU**Named dangerous substances - ANNEX I** None of the ingredients is listed.**National regulations:****Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the gastro-intestinal tract through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin. Hazard Category 1

Skin Sens. 1A: Sensitisation - Skin. Hazard Category 1A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

Sources European Chemicals Agency, <http://echa.europa.eu/>