



# Etalon Universal Putty

gb 1/1211

## Technical Data Sheet

page 1 / 1

Etalon Universal Putty is a polyester filling and finishing putty with adhesion on steel, aluminium, galvanized metal and glass fibre reinforced compounds. Fast drying and easy sanding are further features of this top product. The full adhesive power will be first developed after approx. 1 hour when applied on galvanized substrates.

Colour shade	beige		
Mixing ratio	100 : 2		
Hardener	hardener		
Thinners			
Spraying viscosity 20° C			
Application	spraying pressure	spraying nozzle	spraying operations
Air / Flowjar - Spray gun			
Airless / Airmix			
Pot life	3 - 4 min.		
Coat thickness / dry film			
Curing time / Flash off time			
Dry	recoat time	dust dry	set to touch
Object Temp. 20° C	Sandable after approx. 20 min.		
Object Temp. 60° C	Sandable after approx. 5 min.		
VOC content	EU limiting value for the product (cat. B/b): 250 g/l (2007) This product contains max. 6 g/l VOC [ 0.05 lbs/gal]		

**Remarks:**

The substrate must be clean, dry and free of grease. Slightly sand surfaces! Remove old layers of paint or primer, which are not adhesive or fully dry. Do not apply on thermoplastic or acid-containing products. Mix putty and hardener properly.